

## Specification Sheet

Part Number: 596-00862

NOMINAL OPERATING AC VOLTAGE	██████████
NOMINAL OPERATING AC FREQUENCY	██████████
MAXIMUM AC POWER	██████████
MAXIMUM AC CURRENT	██████████
MAX OVERCURRENT DEVICE RATING FOR AC MODULE PROTECTION	██████████

Metal Solar Placard, Engravable, AC Module, 4.0" x 2.0", AA, Black, 5/pkg

**Article Number** 596-00862

**Type** AC2011M5ENG

**Color** Black (BK)

**Features & Benefits**

- Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.
- Aggressive adhesive ensures strong bond, even on powder coated surfaces.
- Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability.
- Optional Paint Shields provide additional protection for pre-printed and variable data placards.

**Quantity Per** pack

<b>Product Description</b>	Variable data placards are used to mark areas specific to the individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, engravable placards are designed to meet industry codes. Engravable placards have a black area that can be engraved using standard engraving equipment.
<b>Short Description</b>	Metal Solar Placard, Engravable, AC Module, 4.0" x 2.0", AA, Black, 5/pkg
<b>Global Part Name</b>	AC2011M5ENG-AA-BK
<b>Technical Description</b>	4" X 2" Black text on aluminum background that reads as: "NOMINAL AC VOLTAGE;NOMINAL OPERATING AC FREQUENCY;MAXIMUM AC POWER;MAXIMUM AC CURRENT;MAXIMUM OVERCURRENT DEVICE RATING FOR AC MODULE PROTECTION." 10 per pack. Nameplate can be used with standard engraving equipment to add variable data.
<b>Length L (Imperial)</b>	4.0
<b>Length L (Metric)</b>	101.6
<b>Width W (Imperial)</b>	4.0
<b>Width W (Metric)</b>	101.6
<b>Height H (Imperial)</b>	2.0
<b>Height H (Metric)</b>	50.80
<b>Material</b>	Anodized Aluminum (AA)

<b>Material Shortcut</b>	AA
<b>Adhesive</b>	Ultra High Bond Permanent Acrylic Adhesive
<b>Halogen free</b>	No
<b>Adhesive Operating Temperature</b>	from +50°F (from +10°C)
<b>Operating Temperature (Metric)</b>	-40°F to +203°F (-40°C to +95°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	NEC2017 NEC2014
<b>Warranty (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	5
<b>Package Quantity (Metric)</b>	5
<b>Customs Number</b>	7616995195
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	.104
<b>Weight (Imperial)</b>	0.23

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)