


## **Specification Sheet**

Part Number: 596-00918

**Article Number** 

**Quantity Per** 



Metal Solar Placard, Hand Writable, DC Module, 3.75" x 1.75", AA, Black, 5/pkg

596-00918

pack

Article Number	390-00916
Туре	DC2017M5
Color	Black (BK)
Features & Benefits	<ul> <li>Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.</li> <li>Aggressive adhesive ensures strong bond, even on powder coated surfaces.</li> <li>Meets or exceeds NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability.</li> <li>Optional Paint Shields provide additional protection for pre-printed and variable data placards.</li> </ul>

_			_	_			
ם	rn	a	Inct	Des	2 C F I	nt	ınn
	ıv	u	uCL	DE	3 G I I	IJι	IUII

Variable data placards are used to mark areas specific to the individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, HellermannTyton offers two styles of variable placards: hand-writable and engravable. Both hand-writable placards feature a silver variable data area that can be marked using an industrial paint pen. Engravable placards have a black area that can be engraved using standard engraving equipment.

**Short Description** 

Metal Solar Placard, Hand Writable, DC Module, 3.75" x 1.75", AA, Black, 5/pkg

**Global Part Name** 

DC2017M5-AA-BK

**Technical Description** 

3.75" X 1.75" Silver aluminum text on black background that reads as: "MAXIMUM VOLTAGE; MAXIMUM CIRCUIT CURRENT; MAX RATED OUTPUT CURRENT OF THE CHARGE CONTROLLER OR DC-TO-DC CONVERTER (IF INSTALLED)." 5 per pack. Nameplate is also printable using a paint pen to add the variable voltage information on demand.

Length L (Imperial)

1.75

Length L (Metric)

44.45

Width W (Imperial)

3.75

Width W (Metric)

95.25

Thickness T (Metric)

64.0

Height H (Imperial)

1.75

Height H (Metric)

44.45

Material

Anodized Aluminum (AA)

**Material Shortcut** 

AA

**Adhesive** 

Ultra High Bond Permanent Acrylic Adhesive

Halogen free

No

**Adhesive Operating Temperature** 

from +50°F (from +10°C)

**Operating Temperature (Metric)** 

-40°F to +203°F (-40°C to +95°C)

Reach Complaint(Article 33)

Yes

**ROHS Complaint** 

Yes

**Certification/Specification WEB** 

NEC2017

Warranty (US)

Yes

Package Quantity(Imperial)

5

**Package Quantity (Metric)** 

5

**Customs Number** 

3919102055

Labels per Column

1

Labels per Row

1

Weight (Metric) .104
Weight (Imperial) 0.23

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions