

Specification Sheet

Part Number: CTN1120STD



Convoluted Tubing, Slit, 1.5" Dia, PA6, Black with Gray Stripe, 150ft/carton

Article Number	169-60003

Type CTN1120

Color Black with Gray Stripe (BKSTGY)

Features & Benefits

• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture • Tubing protects cables and wires against automotive fluids, vibration wear • Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight

Quantity Per carton

_			_	_				
ם	rn	a	Inct	Des	2 C Fi	ınt	10	n
	ıv	u	uCL	DC	36II	IDL	ıv	

HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description

Convoluted Tubing, Slit, 1.5" Dia, PA6, Black with Gray Stripe, 150ft/carton

Global Part Name

CTN1120-PA6-BK

Technical Description

Convoluted Tubing, Slit, 1-1/2" Dia., PA6, Black w/Gray Stripe

Length L (Imperial)

150.0

Length L (Metric)

45.7

Variant

Slit

Inner Diameter D (Imperial)

1.647

Inner Diameter D (Metric)

41.83

Diameter D (imperial)

1.947

Diameter D (metric)

49.45

Outside Diameter OD(Imperial)

1.947

Outside Diameter OD(metric)

49.45

Nominal Diameter (Imperial)	1.5
Nominal Diameter (Metric)	38.1
Wall Thickness WT (Imperial)	0.006
Wall Thickness WT (Metric)	0.152
Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL 94 HB
Halogen free	No
Operating Temperature (Metric)	-40°F to +257°F (-40°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	150
Package Quantity (Metric)	45.72
Customs Number	3926909988

