

## **Specification Sheet**

Part Number: CTN1140STD



Convoluted Tubing, Slit, 1.25" Dia, PA6, Black with Gray Stripe, 250 ft/carton

Article Number	169-60005

Type CTN1140

**Color** Black with Gray Stripe (BKSTGY)

Features & Benefits

• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture • Tubing protects cables and wires against automotive fluids, vibration wear • Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight

Quantity Per carton

HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

**Short Description** 

Convoluted Tubing, Slit, 1.25" Dia, PA6, Black with Gray Stripe, 250 ft/carton

**Global Part Name** 

CTN1140-PA6-BK

**Technical Description** 

Convoluted Tubing, Slit, 1-1/4" Dia., PA6, Black w/Gray Stripe

Length L (Imperial)

250.0

Length L (Metric)

76.2

**Variant** 

Slit

**Inner Diameter D (Imperial)** 

1.257

**Inner Diameter D (Metric)** 

31.93

Diameter D (imperial)

1.50

**Diameter D (metric)** 

38.10

**Outside Diameter OD(Imperial)** 

1.50

**Outside Diameter OD(metric)** 

38.10

Nominal Diameter (Imperial)	1.25
Nominal Diameter (Metric)	31.75
Wall Thickness WT (Imperial)	0.006
Wall Thickness WT (Metric)	0.152
Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL 94 HB
Halogen free	No
Operating Temperature (Metric)	-40°F to +257°F (-40°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	250
Package Quantity (Metric)	76.20
Customs Number	3926909988

