

Specification Sheet

Part Number: CTN120STD



Convoluted Tubing, Slit, .5" Dia, PA6, Black with Gray Stripe, 1100 ft/carton

Article Number	169-60007
Type	CTN120
Color	Black with Gray Stripe (BKSTGY)
Features & Benefits	<ul style="list-style-type: none"><li>• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture</li><li>• Tubing protects cables and wires against automotive fluids, vibration wear</li><li>• Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight</li></ul>
Quantity Per	carton

<b>Product Description</b>	HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
<b>Short Description</b>	Convoluted Tubing, Slit, .5" Dia, PA6, Black with Gray Stripe, 1100 ft/carton
<b>Global Part Name</b>	CTN120-PA6-BK
<b>Technical Description</b>	Convoluted Tubing, Slit, 1/2" Dia., PA6, Black w/Gray Stripe
<b>Length L (Imperial)</b>	1100.0
<b>Length L (Metric)</b>	335.3
<b>Variant</b>	Slit
<b>Width W (Imperial)</b>	0.127
<b>Width W (Metric)</b>	3.23
<b>Inner Diameter D (Imperial)</b>	0.516
<b>Inner Diameter D (Metric)</b>	13.11
<b>Diameter D (imperial)</b>	0.70
<b>Diameter D (metric)</b>	17.78

<b>Outside Diameter OD(Imperial)</b>	0.70
<b>Outside Diameter OD(metric)</b>	17.78
<b>Nominal Diameter (Imperial)</b>	0.5
<b>Nominal Diameter (Metric)</b>	12.70
<b>Wall Thickness WT (Imperial)</b>	0.005
<b>Wall Thickness WT (Metric)</b>	0.127
<b>Material</b>	Polyamide 6 (PA6)
<b>Material Shortcut</b>	PA6
<b>Flammability</b>	UL 94 HB
<b>Halogen free</b>	No
<b>Operating Temperature (Metric)</b>	-40°F to +257°F (-40°C to +125°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	1100

Package Quantity (Metric)	335.30
Customs Number	3926909988