

Specification Sheet

Part Number: CTN140STD



Convoluted Tubing, Slit, .25" Dia, PA6, Black with Gray Stripe, 3200 ft/carton

Article Number	169-60009
Type	CTN140
Color	Black with Gray Stripe (BKSTGY)
Features & Benefits	<ul style="list-style-type: none">• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture• Tubing protects cables and wires against automotive fluids, vibration wear• Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight
Quantity Per	carton

Product Description	HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Short Description	Convoluted Tubing, Slit, .25" Dia, PA6, Black with Gray Stripe, 3200 ft/carton
Global Part Name	CTN140-PA6-BK
Technical Description	Convoluted Tubing, Slit, 1/4" Dia., PA6, Black w/Gray Stripe
Length L (Imperial)	3200.0
Length L (Metric)	975.4
Variant	Slit
Inner Diameter D (Imperial)	0.276
Inner Diameter D (Metric)	7.01
Diameter D (imperial)	0.398
Diameter D (metric)	10.11
Outside Diameter OD(Imperial)	0.398
Outside Diameter OD(metric)	10.11

Nominal Diameter (Imperial)	0.25
Nominal Diameter (Metric)	6.35
Wall Thickness WT (Imperial)	0.004
Wall Thickness WT (Metric)	0.102
Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL 94 HB
Halogen free	No
Operating Temperature (Metric)	-40°F to +257°F (-40°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	3200
Package Quantity (Metric)	975.40
Customs Number	3926909988

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)