HellermannTyton

Specification Sheet

Part Number: CTP10



Convoluted Tubing, Slit, 1" Dia, PE, Black, 2250 ft/carton

Article Number 169-60500

Type CTP10

Color Black (BK)

Features & Benefits

• Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install. • Tubing provides full coverage where spiral wrap or other coverings may not be suitable. • In harsh applications the tubing provides resistance to crushing, impact, and abrasion. • Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Quantity Per carton

_			_	_			
ם	rn	a	Inct	Des	2 C F I	nt	ınn
	ıv	u	uCL	DE	3 G I I	IJι	IUII

HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description

Convoluted Tubing, Slit, 1" Dia, PE, Black, 2250 ft/carton

Global Part Name

CTP10-PE-BK

Technical Description

Convoluted Tubing, Slit, 1" Dia., PE, Black

Length L (Imperial)

2250.0

Length L (Metric)

685.8

Variant

Slit

Inner Diameter D (Imperial)

1.069

Inner Diameter D (Metric)

27.16

Diameter D (imperial)

1.304

Diameter D (metric)

33.13

Outside Diameter OD(Imperial)

1.304

Outside Diameter OD(metric)

33.13

Nominal Diameter (Imperial) 1 **Nominal Diameter (Metric)** 25.4 Wall Thickness WT (Imperial) 0.006 Wall Thickness WT (Metric) 0.152 Material Polyethylene (PE) **Material Shortcut** PΕ **Flammability** Not Flame Retardant Halogen free No **Operating Temperature (Metric)** -40°F to +185°F (-40°C to +85°C) Reach Complaint(Article 33) Yes **ROHS Complaint** Yes Package Quantity(Imperial) 2250 Package Quantity (Metric) 685.80

3926909988

Customs Number

