## **HellermannTyton**

## **Specification Sheet**

Part Number: CTP1120STD



Convoluted Tubing, Slit, 1.5" Dia, PE, Black, 150ft/carton

Article Number 169-60503

Type CTP1120

Color Black (BK)

**Features & Benefits** 

• Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install. • Tubing provides full coverage where spiral wrap or other coverings may not be suitable. • In harsh applications the tubing provides resistance to crushing, impact, and abrasion. • Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Quantity Per carton

_				_				
Pı	n	du	rt.	D	esc	rin	tic	۱n

HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

**Short Description** 

Convoluted Tubing, Slit, 1.5" Dia, PE, Black, 150ft/carton

**Global Part Name** 

CTP1120-PE-BK

**Technical Description** 

Convoluted Tubing, Slit, 1-1/2" Dia., PE, Black

Length L (Imperial)

150.0

Length L (Metric)

45.7

Variant

Slit

**Inner Diameter D (Imperial)** 

1.647

Inner Diameter D (Metric)

41.83

Diameter D (imperial)

1.947

Diameter D (metric)

49.45

**Outside Diameter OD(Imperial)** 

1.947

**Outside Diameter OD(metric)** 

49.45

Nominal Diameter (Imperial)	1.5		
Nominal Diameter (Metric)	38.1		
Wall Thickness WT (Imperial)	0.006		
Wall Thickness WT (Metric)	0.152		
Material	Polyethylene (PE)		
Material Shortcut	PE		
Flammability	Not Flame Retardant		
Halogen free	No		
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)		
Reach Complaint(Article 33)	Yes		
ROHS Complaint	Yes		
Package Quantity(Imperial)	150		
Package Quantity (Metric)	45.72		
Customs Number	3926909988		

