HellermannTyton

Specification Sheet

Part Number: CTP1140



Convoluted Tubing, Slit, 1.25" Dia, PE, Black, 1800 ft/carton

Article Number	169-60504
Туре	CTP1140
Color	Black (BK)
Features & Benefits	• Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install. • Tubing provides full coverage where spiral wrap or other coverings may not be suitable. • In harsh applications the tubing provides resistance to crushing, impact, and abrasion. • Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.
Quantity Per	carton

Product Description	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Short Description	Convoluted Tubing, Slit, 1.25" Dia, PE, Black, 1800 ft/carton
Global Part Name	CTP1140-PE-BK
Technical Description	Convoluted Tubing, Slit, 1-1/4" Dia., PE, Black
Length L (Imperial)	1800.0
Length L (Metric)	548.6
Variant	Slit
Inner Diameter D (Imperial)	1.257
Inner Diameter D (Metric)	31.93
Diameter D (imperial)	1.50
Diameter D (metric)	38.10
Outside Diameter OD(Imperial)	1.50

Outside Diameter OD(metric) 38.10

Nominal Diameter (Imperial)	1.25
Nominal Diameter (Metric)	31.75
Wall Thickness WT (Imperial)	0.006
Wall Thickness WT (Metric)	0.152
Material	Polyethylene (PE)
Material Shortcut	PE
Flammability	Not Flame Retardant
Halogen free	No
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	1800
Package Quantity (Metric)	548.60
Customs Number	3926909988

© 2020 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions