

Specification Sheet

Part Number: CTP580



Convoluted Tubing, Slit, .63" Dia, PE, Black, 5500 ft/carton

Article Number	169-60516
Type	CTP580
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.</li><li>• Tubing provides full coverage where spiral wrap or other coverings may not be suitable.</li><li>• In harsh applications the tubing provides resistance to crushing, impact, and abrasion.</li><li>• Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.</li></ul>
Quantity Per	carton

<b>Product Description</b>	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
<b>Short Description</b>	Convoluted Tubing, Slit, .63" Dia, PE, Black, 5500 ft/carton
<b>Global Part Name</b>	CTP580-PE-BK
<b>Technical Description</b>	Convoluted Tubing, Slit, 5/8" Dia., PE, Black
<b>Length L (Imperial)</b>	5500.0
<b>Length L (Metric)</b>	1676.4
<b>Variant</b>	Slit
<b>Inner Diameter D (Imperial)</b>	0.639
<b>Inner Diameter D (Metric)</b>	16.23
<b>Diameter D (imperial)</b>	0.837
<b>Diameter D (metric)</b>	21.26
<b>Outside Diameter OD(Imperial)</b>	0.837
<b>Outside Diameter OD(metric)</b>	21.26

<b>Nominal Diameter (Imperial)</b>	0.63
<b>Nominal Diameter (Metric)</b>	16.00
<b>Wall Thickness WT (Imperial)</b>	0.005
<b>Wall Thickness WT (Metric)</b>	0.127
<b>Material</b>	Polyethylene (PE)
<b>Material Shortcut</b>	PE
<b>Flammability</b>	Not Flame Retardant
<b>Halogen free</b>	No
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	5500
<b>Package Quantity (Metric)</b>	1676.40
<b>Customs Number</b>	3926909988

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)