

Specification Sheet

Part Number: CTT60R0C2



Clamp Tie, 8" Long, 60lb Tensile Strength, PA66, Black, 100/pkg

Article Number	112-56019
----------------	-----------

Type	CTT60R
------	--------

Color	Black (BK)
-------	------------

Features & Benefits	• Head design contains clamping rails to provide full circumferential compression around bundles. • Bent tail allows for quick insertion into head.
---------------------	---

Quantity Per	bag
--------------	-----

Product Description	HellermannTyton clamp tie has triangular shaped tabs extending beneath the head for optimal surface contact and complete circumferential compression to 360 degrees. The bent tail design allows quick and simple installations by hand. The clamps are recommended for soft rubber hose applications including fuel, water, and air vacuum lines.
---------------------	---

Short Description	Clamp Tie, 8" Long, 60lb Tensile Strength, PA66, Black, 100/pkg
Global Part Name	CTT60R-PA66-BK
Minimum Tensile Strength (Imperial)	60.0
Minimum Tensile Strength (Metric)	267.0
Length L (Imperial)	8.0
Length L (Metric)	203.2
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.77
Bundle Diameter Max (Metric)	45.0

Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL ANSI/UL 62275 UL ANSI/UL 1565 UL ANSI/UL 746B
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

Content Unit(BMEcat)	pcs.
Weight (Metric)	0.0013
Weight (Imperial)	0.0028