

Specification Sheet

Part Number: HDM321HIHSUVH4



Medium Torque Cable Tie Mount, Mounting Dia. 0.3125", Max Torque 40.0 lb - ft, PA66HIRHSUV, Black, 500/pkg

Article Number	151-07100
-----------------------	-----------

Type	HDM321
-------------	--------

Color	Black (BK)
--------------	------------

Features & Benefits	• Mount and tie combination makes it easy to service bundles in the field. • Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments. • Eliminates the needs for multiple sized fix diameter clamps.
--------------------------------	---

Quantity Per	bag
---------------------	-----

Product Description	The arched H-profile of the saddle surface allows for a broad surface contact with the bundle, minimizing pinching and crushing of the bundles, and adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.
Short Description	Medium Torque Cable Tie Mount, Mounting Dia. 0.3125", Max Torque 40.0 lb - ft, PA66HIRHSUV, Black, 500/pkg
Global Part Name	HDM321-PA66HIRHSUV-BK
Length L (Imperial)	1.81
Length L (Metric)	46.0
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.95
Width W (Metric)	24.0
Height H (Imperial)	0.81
Height H (Metric)	20.7
Cable Tie Width Max (Imperial)	0.50
Cable Tie Width Max (Metric)	12.7
Mounting Hole Diameter D (Imperial)	0.3125
Mounting Hole Diameter D (Metric)	8.31 mm

Mounting Hole Diameter D Min (Imperial) 0.3125

Mounting Hole Diameter D Max (Imperial) 0.3125

Mounting Hole Diameter D Max (Metric) 7.9

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL 94 HB

Operating Temperature (Metric) -40°F to +221°F (-40°C to +105°C)

Maximum Torque (kgf-cm) 553

Maximum Torque (lbf-ft) 40

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

Content Unit(BMEcat)	pcs.
Weight (Imperial)	0.01902