

Specification Sheet

Part Number: LKCRF19H4



Low Profile Rivet Mount, .938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 500/pkg

Article Number	151-27009
-----------------------	-----------

Type	LKCRF1
-------------	--------

Color	Natural (NA)
--------------	--------------

Features & Benefits	• The low-profile rivet mount is designed to secure wiring bundles and fastens with the drive rivet through a predrilled hole. • This mount is ideal for use in applications where space is limited.
--------------------------------	--

Quantity Per	bag
---------------------	-----

Product Description	HellermannTyton's Mounts with Rivets are ideal for use in applications where space is limited and is designed to secure wiring bundles. Fastens with the drive rivet through a predrilled hole.
----------------------------	---

Short Description	Low Profile Rivet Mount, .938" x .47", 0.25" Hole, Max Pan .134", T18-T50 Ties, 500/pkg
Global Part Name	LKCRF1-PA66-NA
Length L (Imperial)	0.938
Length L (Metric)	24.0
Fixation Method	with Rivet (Mounts)
Width W (Imperial)	0.47
Width W (Metric)	12.0
Cable Ties	T18 - T50
Height H (Imperial)	0.157
Height H (Metric)	4.0
Cable Tie Width Max (Imperial)	0.18
Cable Tie Width Max (Metric)	4.8
Panel Thickness Max(Imperial)	0.134
Panel Thickness Max (Metric)	3.40
Mounting Hole Diameter D (Imperial)	0.25

Mounting Hole Diameter D (Metric) 6.5 mm

Mounting Hole Diameter D Max (Metric) 6.5

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Operating Temperature (Metric) -40°F to +185°F (-40°C to +85°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

Content Unit(BMEcat) pcs.