

## Specification Sheet

Part Number: SNP12AGHS0M4



Snapper Hose Clamp, .62"—.72" Bundle Diameter, PA66GF13, Black, 1000/pkg

|                       |           |
|-----------------------|-----------|
| <b>Article Number</b> | 190-00255 |
|-----------------------|-----------|

|             |        |
|-------------|--------|
| <b>Type</b> | SNP12A |
|-------------|--------|

|              |            |
|--------------|------------|
| <b>Color</b> | Black (BK) |
|--------------|------------|

|                                |  |
|--------------------------------|--|
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• Designed for quick, ratcheted installation and can be released and reused.</li><li>• Heat stabilized material is suitable for high temperature applications.</li></ul> |
|--------------------------------|--|

|                     |     |
|---------------------|-----|
| <b>Quantity Per</b> | bag |
|---------------------|-----|

|                            |  |
|----------------------------|--|
| <b>Product Description</b> | HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes. |
|----------------------------|--|

|                                       |  |
|---------------------------------------|--|
| <b>Short Description</b>              | Snapper Hose Clamp, .62"—.72" Bundle Diameter, PA66GF13, Black, 1000/pkg |
| <b>Global Part Name</b>               | SNP12A-PA66GF13-BK   |
| <b>Fixation Method</b>                | Plug-in mounting   |
| <b>Variant</b>                        | Closed   |
| <b>Wall Thickness WT (Imperial)</b>   | .070   |
| <b>Wall Thickness WT (Metric)</b>     | 1.78   |
| <b>Material</b>                       | Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)   |
| <b>Material Shortcut</b>              | PA66GF13   |
| <b>Flammability</b>                   | UL 94 HB   |
| <b>UV Resistant (Yes/No)</b>          | No   |
| <b>Operating Temperature (Metric)</b> | -40°F to +221°F (-40°C to +105°C)  |
| <b>ROHS Complaint</b>                 | Yes  |
| <b>Package Quantity(Imperial)</b>     | 1000   |

|                           |            |
|---------------------------|------------|
| Package Quantity (Metric) | 1000       |
| Customs Number            | 3926909988 |