

Specification Sheet

Part Number: T120R0PPH4



Cable Tie, 15" Long, 60lb Tensile Strength, PP, Black, 500/pkg

Article Number	111-12066
Type	T120R
Color	Black (BK)
Features & Benefits	• Polypropylene cable ties deliver excellent resistance to chemicals and salts. • Inside serrations provide strong grip on cables and wire bundles. • Easy application either manually or with a tensioning tool. • Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description	HellermannTyton's polypropylene cable ties offer added resistance to most chemicals. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Cable Tie, 15" Long, 60lb Tensile Strength, PP, Black, 500/pkg
Global Part Name	T120R-PP-BK
Minimum Tensile Strength (Imperial)	60.0
Minimum Tensile Strength (Metric)	267.0
Length L (Imperial)	15.0
Length L (Metric)	387.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.30
Width W (Metric)	7.6
Bundle Diameter Min (Imperial)	0.50

Bundle Diameter Min (Metric)	12.7
Bundle Diameter Max (Imperial)	4.13
Bundle Diameter Max (Metric)	105.0
Thickness T (Imperial)	0.07
Thickness T (Metric)	1.8
Material	Polypropylene (PP)
Material Shortcut	PP
Flammability	UL 94 HB
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +239°F (-40°C to +115°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500

Customs Number	3926909988
-----------------------	------------

Content Unit(BMEcat)	pcs.
-----------------------------	------

Weight (Metric)	5.2
------------------------	-----