

Specification Sheet

Part Number: T120RSM0HIRK2



Stud Mount Tie for .25", 120lb Tensile, 16.0" Long, PA66HIRHSUV, Black, 50/pkg

Article Number	157-01300
Type	T120RSM
Color	Black (BK)
Features & Benefits	•Covers top of stud for protection from stud end. •Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure. •PA46 material option allows use in high-heat applications.
Quantity Per	bag
Product Description	HellermannTyton stud mount tie designed for use on a 1/4" threaded stud or exposed threads of a machine screw.

Short Description	Stud Mount Tie for .25", 120lb Tensile, 16.0" Long, PA66HIRHSUV, Black, 50/pkg
Global Part Name	T120RSM-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	120.0
Minimum Tensile Strength (Metric)	535.0
Length L (Imperial)	16.0
Length L (Metric)	405.0
Fixation Method	Weld Stud Fixing
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.3
Width W (Metric)	7.6
Bundle Diameter Min (Imperial)	0.20
Bundle Diameter Min (Metric)	5.0

Bundle Diameter Max (Imperial)	3.98
Bundle Diameter Max (Metric)	101.0
Height H (Imperial)	.77
Height H (Metric)	19.50
Stud Diameter (Metric)	6.3 mm
Stud Diamater (Imperial)	0.25
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988

