


Specification Sheet

Part Number: T18S9C2



Cable Tie, 3.3" Long, UL Rated, 18lb Tensile Strength, PA66, Natural, 100/pkg

Article Number	111-02805
Type	T18S
Color	Natural (NA)
Features & Benefits	• Inside serrations allow for strong grip on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Quantity Per	bag
Product Description	T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Cable Tie, 3.3" Long, UL Rated, 18lb Tensile Strength, PA66, Natural, 100/pkg
Global Part Name	T18S-PA66-NA
Minimum Tensile Strength (Imperial)	18.0
Minimum Tensile Strength (Metric)	80
Length L (Imperial)	3.27
Length L (Metric)	83.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.09
Width W (Metric)	2.3
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	0.63

Bundle Diameter Max (Metric)	16.0
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
Certification/Specification WEB	UL ANSI/UL 62275 DNV GL IEC 62275:2006
UL Recognized (US)	Yes
UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes
UL Listed (US	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100

