

Specification Sheet

Part Number: TAG68L-789



Laser Tag Label, 3.8" x .275", 70 Per sheet, PET, White, 2500/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 594-68789                                                                                                                                                                                                                                                                                                                                                                    |
| Type                | TAG68L                                                                                                                                                                                                                                                                                                                                                                       |
| Color               | White (WH)                                                                                                                                                                                                                                                                                                                                                                   |
| Features & Benefits | <ul style="list-style-type: none"><li>• Laser printable white polyester has a smooth surface, allowing for the highest resolution and print contrast.</li><li>• The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.</li><li>• Lasertags are not affected by the high heat required in a laser printer.</li></ul> |
| Quantity Per        | pack                                                                                                                                                                                                                                                                                                                                                                         |

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Description</b>            | HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 789 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking. |
| <b>Short Description</b>              | Laser Tag Label, 3.8" x .275", 70 Per sheet, PET, White, 2500/pkg                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Global Part Name</b>               | TAG68L-789-WH                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Width W (Imperial)</b>             | 3.8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Width W (Metric)</b>               | 96.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Bundle Diameter Min (Imperial)</b> | .15                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Bundle Diameter Min (Metric)</b>   | 3.80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Thickness T (Metric)</b>           | 64.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Height H (Imperial)</b>            | 0.275                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Height H (Metric)</b>              | 6.98                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Material</b>                       | Type 789, Polyester (789)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Material Shortcut</b>              | 789                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Adhesive</b>                       | Acrylic                           |
| <b>Halogen free</b>                   | No                                |
| <b>Adhesive Operating Temperature</b> | -40°F to +302°F (-40°C to +150°C) |
| <b>Operating Temperature (Metric)</b> | -40°F to +300°F (-40°C to +149°C) |
| <b>Reach Complaint(Article 33)</b>    | Yes                               |
| <b>ROHS Complaint</b>                 | Yes                               |
| <b>Package Quantity(Imperial)</b>     | 2500                              |
| <b>Package Quantity (Metric)</b>      | 2500                              |
| <b>Customs Number</b>                 | 3919905060                        |
| <b>Labels per Column</b>              | 35                                |
| <b>Labels per Row</b>                 | 2                                 |
| <b>Weight (Metric)</b>                | 0.521                             |
| <b>Weight (Imperial)</b>              | 1.14                              |