

Specification Sheet

Part Number: TSR2W-36



End Cap, 1-1/4", 2-Piece, PVC, White, 10 Individual/bag

|                     |  |
|---------------------|--|
| Article Number      | 250-02362  |
| Type                | TSR2-36  |
| Color               | White (WH)   |
| Features & Benefits | <ul style="list-style-type: none"><li>• Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.</li><li>• PVC construction is lightweight, durable and more affordable than metallic raceway systems.</li><li>• Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing.</li><li>• Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor.</li><li>• Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.</li></ul> |
| Quantity Per        | bag  |

|                                       |  |
|---------------------------------------|--|
| <b>Product Description</b>            | HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations. TSR surface raceway systems can be used to route a variety of communication cable, including high speed UTP and fiber optic cable. |
| <b>Short Description</b>              | End Cap, 1-1/4", 2-Piece, PVC, White, 10 Individual/bag  |
| <b>Global Part Name</b>               | TSR2-36-PVC-WH   |
| <b>Material</b>                       | Polyvinylchloride (PVC)  |
| <b>Material Shortcut</b>              | PVC  |
| <b>Flammability</b>                   | UL 94 V0   |
| <b>Halogen free</b>                   | No   |
| <b>Operating Temperature (Metric)</b> | +122°F (+50°C)   |
| <b>Reach Complaint(Article 33)</b>    | No   |
| <b>ROHS Complaint</b>                 | Yes  |
| <b>Package Quantity(Imperial)</b>     | 10   |

|                           |            |
|---------------------------|------------|
| Package Quantity (Metric) | 10         |
| Customs Number            | 3925900000 |