HellermannTyton

Specification Sheet

Part Number: TSR3FW-14

Splice Cover, 1-3/4", PVC, 2-Piece, Office White, 10 Individual/bag

Article Number	250-03140
Type	TSR3-14
Color	Office White (OEWH)
Features & Benefits	• Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance. • PVC construction is lightweight, durable and more affordable than metallic raceway systems. • Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing. • Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor. • Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.
Quantity Per	bag

Product Description

HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations. TSR surface raceway systems can be used to route a variety of communication cable, including high speed UTP and fiber optic cable.

Short Description

Splice Cover, 1-3/4", PVC, 2-Piece, Office White, 10 Individual/bag

Global Part Name

TSR3-14-PVC-WH

Material

Polyvinylchloride (PVC)

Material Shortcut

PVC

Flammability

UL 94 V0

Halogen free

No

Operating Temperature (Metric)

+122°F (+50°C)

Reach Complaint(Article 33)

No

ROHS Complaint

Yes

Package Quantity(Imperial)

10

Package Quantity (Metric)   10

Customs Number   3925900000

Contact Us   RoHS/WEEE Compliance   Disclaimer   Terms and Conditions