

Specification Sheet

Part Number: TSRP2FW-8A



One Piece Power Rated Raceway, 1-1/4", 8.0 ft Long, PVC, Office White, 160ft/Carton

Article Number	250-62800
Type	TSRP2-8A
Color	Office White (OEWH)
Features & Benefits	• Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick re-entry as well as providing a secure installation of power cables. • U.L. Listed for power up to 600 Volts, meeting UL5A and CSA 22.2 Number 62-93 Standards. • Manufactured from UL 94V-0 rated PVC material. • Fittings incorporate a minimum 1" bend radius per TIA/EIA 568-B and 569-A standards. • Large base for greater adhesive surface. • Rubber-based foam tape adhesive with high ultimate bond strength, which conforms to any surface. • Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking. • Junction boxes can be used for electrical or data outlets. • Designed to complement HellermannTyton's industry standard TSR low voltage raceway system.

Quantity Per	carton
Product Description	HellermannTyton's TSRP power surface raceway is a one piece, non-metallic, adhesive backed latching raceway designed to aesthetically organize and route either power or communications cables. Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick reentry as well as providing a secure installation of power cables.
Short Description	One Piece Power Rated Raceway, 1-1/4", 8.0 ft Long, PVC, Office White, 160ft/Carton
Global Part Name	TSRP2-8A-PVC-WH
Length L (Imperial)	8.0
Length L (Metric)	2.44
Width W (Imperial)	1.25
Width W (Metric)	31.75
Height H (Imperial)	.75
Height H (Metric)	19.05
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC

Flammability	UL 94 V0
Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)
Reach Complaint(Article 33)	No
ROHS Complaint	Yes
UL Listed (US and Canada)	Yes
UL Listed (US	Yes
Package Quantity(Imperial)	160
Package Quantity (Metric)	48.80
Customs Number	3925900000