

Specification Sheet

Part Number: TSRP2W-12



Reducer, 1-3/4" to 3/4" (TSRP3 to TSRP1), PVC, White, 10 Individual/pkg

| | |
|-----------------------|-----------|
| Article Number | 250-62122 |
|-----------------------|-----------|

| | |
|-------------|----------|
| Type | TSRP2-12 |
|-------------|----------|

| | |
|--------------|------------|
| Color | White (WH) |
|--------------|------------|

Features & Benefits

- Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.
- PVC construction is lightweight, durable and more affordable than metallic raceway systems.
- Flexible hinge designed to reduce stress cracking and discoloration from repeated opening and closing.
- Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor.
- Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.
- TSRP power rated surface raceway systems have an enhanced "channel and lug" mating design that provides a tighter, more secure fit between raceway lengths and fittings, enabling the system to be UL Listed for power up to 600 volts and meet UL5A and CSA 22.2.

| | |
|---------------------------------------|---|
| Quantity Per | EA |
| Product Description | <p>HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations. TSRP surface raceway systems are designed to aesthetically organize and route either power or communications cables.</p> |
| Short Description | Reducer, 1-3/4" to 3/4" (TSRP3 to TSRP1), PVC, White, 10 Individual/pkg |
| Global Part Name | TSRP2-12-PVC-WH |
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |
| Flammability | UL 94 V0 |
| Halogen free | No |
| Operating Temperature (Metric) | +122°F (+50°C) |
| Reach Complaint(Article 33) | No |
| ROHS Complaint | Yes |

| | |
|----------------------------------|-----|
| UL Listed (US and Canada) | Yes |
|----------------------------------|-----|

| | |
|----------------------|-----|
| UL Listed (US | Yes |
|----------------------|-----|

| | |
|-----------------------------------|----|
| Package Quantity(Imperial) | 10 |
|-----------------------------------|----|

| | |
|----------------------------------|----|
| Package Quantity (Metric) | 10 |
|----------------------------------|----|

| | |
|-----------------------|------------|
| Customs Number | 3925900000 |
|-----------------------|------------|