

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS		BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS		BY	CHKD	DATE
1	DIS-C-000585		T.K	E.K	07.07.27						

A
A
B
B
C
C
D
D

NOTES

1 APPLICABLE CRIMP CONTACT:HR12-SC-212(CL112-0408-9)
APPLICABLE WIRE:AWG#26 TO #30(COVERED WIRE MAX,OUTSIDE DIA. ϕ 1)
APPLICABLE CONTACT REMOVAL TOOL(EXTRACTION TOOL):HR12-SC-TP(CL150-0050-3)

2 THE RECOMMENDED CLAMP TORQUE OF REF. NO. ⑤ TO BE 2N·m,
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO
PREVENT REF. NO. ⑤ FROM LOOSENING.

3
POLYBUTYLENE TEREPHTHALATE (BLACK) UL94V-0
5
BRASS
NICKEL PLATING

2
STAINLESS STEEL
4
PHOSPHOR BRONZE
NICKEL PLATING

1
ZINC ALLOY
3
MATTE FINISH NICKEL PLATED

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
CODE NO.(OLD) CL		DRAWN M.SATO	DESIGNED T.HORII	CHECKED E.KUNII	APPROVED M.SATO
		'07 04 11	'07 04 11	'07 04 11	'07 04 11

TO	R	F	

DRAWING NO.		PART NO.
SCALE 2 : 1	UNITS mm	HR10G-10R-10SC(71)

CODE NO.	1
CL110-1707-2-71	1

1
2
3
4
FORM NO. 228