APPLICA	BLE STAN	DARD							
OPERATING TEMPERATURE		E RANGE	RANGE   -35 °C TO +85 °C (NOTES 1)   TE		STORAGE TEMPERATU			) °C	
RATING	VOLTAGE		30 V AC		APPLICABLE CONNECTOR		DF37*-40DS-0.4	V (**)	
CURRENT		0.3 A							
			SPECI	IFICAT	IONS				
	EM		TEST METHOD			REG	QUIREMENTS	QT	АТ
-	RUCTION	I			1,000			X	
GENERAL EX	AMINATION		VISUALLY AND BY MEASURING INSTRUMENT.  CONFIRMED VISUALLY.			ACCORDING TO DRAWING.			X
								X	X
ELECTRIC CHARA CONTACT RESISTANCE		20 mV AC OR LESS 1khz,1m A .				2 MAX.		X	<u> </u>
INSULATION RESISTANCE		100 V DC.			50 MΩ	50 MΩ MIN.			-
		100 V AC FOR 1 min.			NO FL	NO FLASHOVER OR BREAKDOWN.			<u> </u>
	NICAL CHA							X	
MECHANICAL OPERATION		500 TIMES INSERTIONS AND EXTRACTIONS.			② NO	<ol> <li>CONTACT RESISTANCE: 100 mΩ MAX.</li> <li>NO DAMAGE, CRACK OR LOOSENESS OF PARTS.</li> </ol>			_
COUN	T D	ESCRIPTI	ON OF REVISIONS		DESIGNED		CHECKED	DA	ATE
								1	
REMARKS	IDE THE TEXT	ERATURE RISING BY CURRENT  ied, refer to JIS C 5402.				APPROVE	D MO. NAKAMURA	07.0	7. 24
INOTE1: INCL	UDE THE TEMP					CHECKED	+	07.0	7. 23
Unless oth	erwise specif					DESIGNEI DRAWN	KY. MIDORIKAWA  KY. MIDORIKAWA	+	)7. 20 )7. 20
					DRAWIN		ELC4-31314	-	
HS	SI	PECIFICATION SHEET			PART NO. DF		37CJ-40DP-0. 4V (53)		
		OSE ELECTRIC CO., LTD.			CODE NO. CL68		4-3049-9-53 🛮 🛕 1/		1/