


APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	VOLTAGE		APPLICABLE CABLE	CABLE DIAMETER : $\phi 6.9\pm 0.3$	
	CURRENT				
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
					
REMARK Unless otherwise specified, refer to JIS C 5402.			APPROVED	AO. SUZUKI	09. 05. 07
			CHECKED	KN. ICHIKAWA	09. 05. 07
			DESIGNED	MO. SHIMOYAMA	09. 05. 07
			DRAWN	MO. SHIMOYAMA	09. 05. 07
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-126674-00		
	SPECIFICATION SHEET		PART NO.	DH-27-CMB (6. 9)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0036-9-00	 1/1