

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICABLE STANDARD		CONTACT NO. / ~ 14		AC 250 V	APPLICABLE CABLES	
RATING	VOLTAGE	DC	0.5 A	V	IMPEDANCE FREQUENCY RANGE Ω (0 ~ Hz)	
	CURRENT				OPERATING TEMPERATURE RANGE °C ~ °C	
	POWER					
	SPECIALTY					

SPECIFICATIONS

NO.	ITEM	CONDITIONS	TEST STANDARD	MIN	MAX	UNITS	QT	AT
1	DESIGN-MATERIAL-FINISH	Applicable Std. and ^{ADC} DC 3-43115		-	-	-	0	0
2	MARKING			-	-	-	0	0
3	INSULATION RESISTANCE	Must be over standard value at DC 500 V.	MIL-STD-202-302 A	500	-	MΩ	0	0
4	CONTACT RESISTANCE	The voltage drop must be under the Std. value at DC 0.1 A.		-	35	mΩ	0	0
	UNIT CONTACT CONTACT	The voltage drop must be under the Std. value at DC A.		-	-	mΩ	-	-
5	DIELECTRIC WITHSTANDING VOLTAGE	Must keep the AC 500 V for one minute.	MIL-STD-202-301	-	-	-	0	0
6	V S W R	Must be under the Std. value at frequency ~ Hz.		-	-	-	-	-
7	INSERTION LOSS	Must be under the Std. value at frequency ~ Hz.		-	-	dB	-	-
8	LOW LEVEL CIRCUIT	The Contact Resistance must be under the Std. value at DC 20mV less and mA.		-	-	mΩ	-	-
9	CONTACT ENGAGEMENT AND SEPARATION FORCES	Must be suitable for the Std. value at applicable gauge. gauge size		-	-	N	-	-
	MATING AND UNMATING FORCES	Must be suitable for the Std. value.		5.49	17.7	N	0	-
10	HUMIDITY	Insulation resistance must be over the Std. value at 40 °C. 90~95 % 96 hours.	MIL-STD-202-103 (B)	1	-	MΩ	0	-
		at high humidity after high humidity		100	-	MΩ	0	-
11	VIBRATION	Must have no damage, crack and looseness of parts at Frequency range 10-55 Hz, Total amplitude 1.52mm, ~ m/s ² at h for directions.	MIL-STD-202-201A	-	-	-	0	-
12	SHOCK	Must have no damage, crack and looseness of parts 490 m/s ² at 3 times for 3 directions.	MIL-STD-202-203B (A)	-	-	-	0	-
13	TEMPERATURE CYCLING	Must have no damage, crack and looseness of parts for -55~85 °C, 5 cycles.	MIL-STD-202-102A (B)	-	-	-	0	-
14	DURABILITY CONTACT	Must be less than the Std. value after 1000 times insertion and extraction at the condition described in above item No.4.		-	35	mΩ	0	-
	CONTACT			-	-	mΩ	-	-
15	SALT SPRAY (CORROSION)	Must not have heavy corrosion after 5% salt water spray for 48 hours.	MIL-STD-202-101D (B)	-	-	-	0	-
16	WATER PRESSURE WITHSTANDING	No leakage at depth m kPa hours.		-	-	-	-	-
17	AIR PRESSURE WITHSTANDING	No leakage at pressure kPa min s		-	-	-	-	-

TO
Q1

REMARKS ① CONTACT RESISTANCE TEST POSITION 	APPROVED A. Nakazawa 92.10.26	 HIROSE ELECTRIC CO., LTD. PART NO. DX30AM-14P CODE NO. CL230-5024-4-	RELEASED
	REVIEWED		
	CHECKED A. Nakazawa 92.10.26		
	DESIGNED S. Iwamoto 92.10.26		
	DRAWN H. Shimizu 92.10.26		
DRAWING NO. SLC4-43115 -	SPECIFICATION SHEET		

