

APPLICABLE STANDARD									
RATING	OPERATING TEMPERATURE RANGE		-55 °C TO 85 °C ⁽¹⁾		STORAGE TEMPERATURE RANGE		-10 °C TO 60 °C ⁽²⁾		
	VOLTAGE		100 V AC		STORAGE HUMIDITY RANGE		40 % TO 70 % ⁽²⁾		
	CURRENT		0.5 A (SIGNAL CONTACT) ⁽³⁾  3 A (MF CONTACT) 		OPERATING HUMIDITY RANGE		RELATIVE HUMIDITY 85% max (NOT DEWED)		
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
CONSTRUCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			x	x
MARKING		CONFIRMED VISUALLY.						x	x
ELECTRIC CHARACTERISTICS									
CONTACT RESISTANCE		100 mA(DC OR 1000Hz)			SIGNAL CONTACT : 90 mΩ MAX. MF CONTACT : 30 mΩ MAX. 			x	—
INSULATION RESISTANCE		250 V DC.			1000 MΩ MIN.			x	—
VOLTAGE PROOF		300 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			x	—
MECHANICAL CHARACTERISTICS									
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE: 40 N MAX. WITHDRAWAL FORCE: 4 N MIN.			x	—
MECHANICAL OPERATION		500 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: SIGNAL CONTACT : 100 mΩ MAX. MF CONTACT : 40 mΩ MAX.  ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			x	—
VIBRATION		FREQUENCY 10 TO 55 TO 10Hz, APPROX 5min SINGLE AMPLITUDE : 0.75 mm, 10 CYCLES FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			x	—
SHOCK		490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.						x	—
ENVIRONMENTAL CHARACTERISTICS									
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.			① CONTACT RESISTANCE: SIGNAL CONTACT : 100 mΩ MAX. MF CONTACT : 40 mΩ MAX. 			x	—
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → +85 °C TIME 30 → 30 min. UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER:WITHIN 2~3 MIN)			② INSULATION RESISTANCE :1000 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			x	—
SULFUR DIOXIDE		EXPOSED AT 25±2°C, 75±5%RH, 25 PPM FOR 96 h. (TEST STANDARD: JIS C 60068)			NO HEAVY CORROSION.			x	—
RESISTANCE TO SOLDERING HEAT		1)REFLOW SOLDERING : PEAK TMP : 260°C MAX REFLOW TMP: 220°C MIN FOR 60sec 2) SOLDERING IRONS : 360°C MAX. FOR 5 sec.			NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL.			x	—
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE 240±3°C FOR IMMERSION DURATION, 3 sec.			A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSSED.			x	—
	COUNT	DESCRIPTION OF REVISIONS			DESIGNED		CHECKED		DATE
	6	DIS-F-004173			TH. SANO		KI. HIROKAWA		09. 09. 15
REMARKS ⁽¹⁾ INCLUDE TEMPERATURE RISE CAUSED BY CURRENT-CARRYING. ⁽²⁾ "STORAGE" MEANS A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE ASSEMBLY TO PCB. ⁽³⁾ THE RATED CURRENT APPLIES TO PER CONTACT. 					APPROVED	HS. OKAWA		09. 04. 28	
					CHECKED	HS. OZAWA		09. 04. 28	
					DESIGNED	KI. HIROKAWA		09. 04. 28	
					DRAWN	KI. HIROKAWA		09. 04. 28	
Unless otherwise specified, refer to JIS-C-5402.									
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAWING NO.		ELC4-159082-00		
		SPECIFICATION SHEET			PART NO.		FX18-60S-0. 8SH		
		HIROSE ELECTRIC CO., LTD.			CODE NO.		CL579-0010-3-00  1/1		