

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
	VOLTAGE	_____	_____	_____	
	CURRENT	_____	APPLICABLE CABLE	φ 10±0.5mm	
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.			-	-
ENVIRONMENTAL CHARACTERISTICS					
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 500 h.		NO HEAVY CORROSION RUIN THE FUNCTION.	X	-
SEALING ⁽¹⁾	EXPOSED AT A DEPTH OF 1.8 m FOR 48 h.		NO WATER PENETRATION INSIDE CONNECTOR.	X	-
AIRTIGHTNESS ⁽¹⁾	APPLY AIR PRESSURE 18 kPa FOR 0.5min TO INSIDE CONNECTOR.		NO AIR BUBBLES INSIDE CONNECTOR.	X	-
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
△					
REMARK NOTES(1) SEALING AND AIRTIGHTNESS SHALL BE TESTED BY APPLICABLE CONNECTOR Unless otherwise specified, refer to JIS C 5402.(IEC 60512)			APPROVED	HY. KOBAYASHI	18.02.26
			CHECKED	HY. KOBAYASHI	18.02.26
			DESIGNED	TH. KAMEYA	18.02.23
			DRAWN	MK. INOUE	18.02.23
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-110458-31-00
HRS	SPECIFICATION SHEET		PART NO.	JR13WCC-10 (31)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL114-2051-3-31	△ 1/1