



Home> Products > Discrete Thermistors > 194 > Product Page

194-104QET-A01



Actual product appearance may vary.

Uni-Curve with insulated leads and epoxy

Features

- Accuracy
- High stability
- Long life
- Cost effective
- Small size
- Epoxy coated

Potential Applications

- Temperature measurement, indication and control
- Compensation of ambient temperature effects on copper coils, transistors, integrated circuits and other semiconductor devices
- Medical

Description

194 Series Thermistors are high quality, low-cost resistance, temperature matched interchangeable units. They offer additional cost savings by eliminating the need for individual resistance temperature calibration, as well as standardization of circuit components and simplification of design and replacement problems. These product are the same as the 192 Series, except the leads are Teflon-coated.

Supporting Documentation

None Available

Product Specifications	
Availability	Global
Nominal Resistance at 25 °C [77 ° F]	100,000 Ohm
Tolerance	± 0,2 °C [0.36 °F]
Accuracy	0 °C to 70 °C [32 °F to 158 °F]
R- T Curve	1
Operating Temperature Range	-60 °C to 150 °C [-76 °F to 302 ° F]
Maximum Diameter	2,413 mm [0.095 in]
Termination Material	30 Gauge solid nickel, Teflon insulated
Lead length	38,1 mm [1.50 in]
Time Constant in Air	15.0 s
Dissipation Constant	0,75 m/W°C
Series Name	194

My Links

- Login to iCOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

Specification Search