



[Home](#) > [Products](#) > [PLL and Registers](#) > [RDIMM](#) > [DDR](#) > [DDR Register](#) > [SSTVA32852A](#) > [SSTVA32852AHT](#)

[Add to myIDT \[?\]](#)

You may also like...

SSTVA32852AHT

Category: [DDR Register](#)
Generic Part: [SSTVA32852A](#)
Market Group: [RDIMM](#)
Description: [DDR 24-BIT TO 48-BIT REGI](#)



Parameters

Package	CABGA 114 (BF114)
Recommended For New Designs	Yes
Package	CABGA 114
Speed	NA
Temperature	C
Voltage	3.3 V
Status	Active
Sample	No
Minimum Order Quantity	2500
Factory Order Increment	2500

Distributor Inventory

Part	Distributor	Qty	Date
SSTVA32852AHT	NU HORIZONS ELECTRONICS	20000	03/04/2008

Documents

Type	Title	Size	Revision Date
Product Change Notice	PCN#: TB-0512-01 Reel Color Changed from Blue to Black	730 KB	12/16/2005
	PCN# : A-0610-02 ASAT China as Alternate Facility for CABGA/CVBGA/FPBGA/TQFP/PQFP	253 KB	10/19/2006

Package

Description	CHIP ARRAY BGA 5.5 X 16.0 MM X 0.8 MM PI
Class	PLASTIC
Moisture Sensitivity Level (MSL)	3
Category	Standard
Moisture Exposure Floor Life	168 hrs. @ <30°C/60%RH
Peak Reflow Temprature	225°C
Rebake Conditions	48 hrs.@125°C
Length	16.0
Mark	H
Width	5.5
Pitch	0.8
Thickness	1.4
Status	Active