



Intel® Celeron® G4900 Processor

2M Cache, 3.10 GHz

☐ Add to Compare

Specifications

Essentials

Performance

Supplemental Information

Memory Specifications

Processor Graphics

Expansion Options

Package Specifications

Advanced Technologies

Security & Reliability

Ordering and Compliance

Compatible products

Downloads and Software

Essentials

📄 Export specifications

Product Collection	Intel® Celeron® Processor G Series
Code Name	Products formerly Coffee Lake
Vertical Segment	Desktop
Processor Number	G4900
Status	Launched
Launch Date ?	Q2'18
Lithography ?	14 nm
Use Conditions ?	Embedded Broad Market Commercial Temp, PC/Client/Tablet
Recommended Customer Price ?	

Performance

# of Cores ?	2
# of Threads ?	2
Processor Base Frequency ?	3.10 GHz
Cache ?	2 MB SmartCache
Bus Speed ?	8 GT/s DMI3
TDP ?	54 W

Supplemental Information

Embedded Options Available ?	Yes
------------------------------	-----

Memory Specifications

Max Memory Size (dependent on memory type) ?	64 GB
Memory Types ?	DDR4-2400
Max # of Memory Channels ?	2
Max Memory Bandwidth ?	37.5 GB/s
ECC Memory Supported ‡ ?	Yes

Processor Graphics

Processor Graphics ‡ ?	Intel® UHD Graphics 610
Graphics Base Frequency ?	350 MHz
Graphics Max Dynamic Frequency ?	1.05 GHz
Graphics Video Max Memory ?	64 GB
4K Support ?	Yes, at 60Hz
Max Resolution (HDMI 1.4)‡ ?	4096x2304@24Hz
Max Resolution (DP)‡ ?	4096x2304@60Hz
Max Resolution (eDP - Integrated Flat Panel)‡ ?	4096x2304@60Hz
DirectX* Support ?	12
OpenGL* Support ?	4.5
Intel® Quick Sync Video ?	Yes
Intel® InTru™ 3D Technology ?	Yes
Intel® Clear Video HD Technology ?	Yes
Intel® Clear Video Technology ?	Yes
# of Displays Supported ‡	3
Device ID	0x3E93

Expansion Options










Scalability	1S Only
PCI Express Revision ?	3.0
PCI Express Configurations ‡ ?	Up to 1x16, 2x8, 1x8+2x4
Max # of PCI Express Lanes ?	16

Package Specifications








Sockets Supported ?	FCLGA1151
Max CPU Configuration	1
Thermal Solution Specification ?	PCG 2015C (65W)
T _{JUNCTION} ?	100°C
Package Size	37.5mm x 37.5mm
Low Halogen Options Available	No

Advanced Technologies

Intel® Optane™ Memory Supported ‡ ?	Yes
Intel® Turbo Boost Technology ‡ ?	No
Intel® vPro™ Platform Eligibility ‡ ?	No
Intel® Hyper-Threading Technology ‡ ?	No
Intel® Virtualization Technology (VT-x) ‡ ?	Yes
Intel® Virtualization Technology for Directed I/O (VT-d) ‡ ?	Yes
Intel® VT-x with Extended Page Tables (EPT) ‡ ?	Yes

Intel® TSX-NI 	No
Intel® 64 ‡ 	Yes
Instruction Set 	64-bit
Instruction Set Extensions 	Intel® SSE4.1, Intel® SSE4.2
Idle States 	Yes
Enhanced Intel SpeedStep® Technology 	Yes
Thermal Monitoring Technologies 	Yes
Intel® Identity Protection Technology ‡ 	Yes
Intel® Stable Image Platform Program (SIPP) 	No

Security & Reliability

Intel® AES New Instructions 	Yes
Secure Key 	Yes
Intel® Software Guard Extensions (Intel® SGX) 	Yes with Intel® ME
Intel® Memory Protection Extensions (Intel® MPX) 	Yes
Intel® OS Guard	Yes
Intel® Trusted Execution Technology ‡ 	No
Execute Disable Bit ‡ 	Yes
Intel® Boot Guard 	Yes

More support options for Intel® Celeron® G4900 Processor (2M Cache, 3.10 GHz)



Product Support



Downloads and Software



Support Community



Warranty and Replacement



Need more help?

Contact support



Give Feedback

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Intel classifications are for informational purposes only and consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company as an importer and/or exporter is responsible for determining the correct classification of your transaction.

Refer to Datasheet for formal definitions of product properties and features.

Downloaded from [Arrow.com](https://www.arrow.com) nputing systems. Please check with the system vendor to determine if your system delivers this feature, or

reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

“Announced” SKUs are not yet available. Please refer to the Launch Date for market availability.

See <http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html?wapkw=hyper+threading> for more information including details on which processors support Intel® HT Technology.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See <http://www.intel.com/content/www/us/en/processors/processor-numbers.html> for details.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.

Check <http://ipt.intel.com/> for systems that support Intel® Identity Protection Technology (Intel® IPT).

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.



[Company Information](#) [Our Commitment](#) [Communities](#) [Investor Relations](#) [Contact Us](#)

[Newsroom](#) [Jobs](#)



[© Intel Corporation](#) | [Terms of Use](#) | [*Trademarks](#) | [Privacy](#) | [Cookies](#) | [Supply Chain Transparency](#) | [Site Map](#)