



Intel® Core™ i7-4700EQ Processor

6M Cache, up to 3.40 GHz

Specifications

Ordering and Compliance

Ordering and spec information

Intel[®] Core[™] i7-4700EQ Processor (6M Cache, up to 3.40 GHz) FC-BGA12F, Tray

Spec Code	SR17L
Ordering Code	CL8064701483802
Shipping Media	TRAY
Stepping	CO
Recommended Customer Price	\$378.00

Trade compliance information

ECCN) 5A992C
CCATS) G077159
US HTS	8542310001

PCN/MDDS Information

	USA (Eng	lish) (⊕	ප	Q
929205	PCN			MDDS	

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Intel classifications are for informational purposes only and consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company as an importer and/or exporter is responsible for determining the correct classification of your transaction.

Refer to Datasheet for formal definitions of product properties and features.

[‡] This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See http://www.intel.com/content/www/us/en/processors/processor-numbers.html for details.

See http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html? wapkw=hyper+threading

for more information including details on which processors support Intel® HT Technology.

Check http://ipt.intel.com/

for systems that support Intel[®] Identity Protection Technology (Intel[®] IPT).

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

Company Information

Our Commitment

https://ark.intel.com/content/www/us/en/ark/products/75469/intel-core-i7-4700eq-processor-6m-cache-up-to-3-40-ghz.html

Communities	USA (English) 🌐 冾 🔍
Investor Relations	
Contact Us	
Newsroom	
Jobs	
f y	
in	
0	
© Intel Corporation	Terms of Use
*Trademarks	Privacy
Cookies	Supply Chain Transparency
Site Map	