Support Home > Product Specifications > Processors

400 MHz

Search specifications





Intel Atom® Processor E3815

Graphics Burst Frequency

512K Cache, 1.46 GHz

Add to Compare

Specifications

Essentials

Performance

Supplemental Information

Memory Specifications

Processor Graphics

Expansion Options

I/O Specifications

Package Specifications


Advanced Technologies

Security & Reliability

Ordering and Compliance

Downloads and Software

Essentials	Export specification:
Product Collection	Intel® Atom™ Processor E Series
Code Name	Products formerly Bay Trail
Vertical Segment	Embedded
Processor Number	E3815
Status	Launched
Launch Date ③	Q4'13
Lithography 🕐	22 nm
Recommended Customer Price ?	
Use Automotive, Industrial Commercial Tem Conditions ?	np, Industrial Extended Temp, Embedded Broad Market Commercial Temp
Performance	
# of Cores ?	1
# of Threads ?	1
Processor Base Frequency 🕐	1.46 GHz
Cache ?	512 KB L2
TDP ?	5 W
Supplemental Information	
Embedded Options Available ?	Yes
Embedded Options Available ? Datasheet	Yes View now
Datasheet	
Datasheet Memory Specifications	View now
Datasheet Memory Specifications Max Memory Size (dependent on memory type) ?	View now
Datasheet Memory Specifications Max Memory Size (dependent on memory type) ? Memory Types ?	View now 8 GB DDR3L 1067
Datasheet Memory Specifications Max Memory Size (dependent on memory type) ? Memory Types ? Max # of Memory Channels ?	View now 8 GB DDR3L 1067
Memory Specifications Max Memory Size (dependent on memory type) ? Memory Types ? Max # of Memory Channels ? ECC Memory Supported † ? Processor Graphics	View now 8 GB DDR3L 1067



More support options for Intel Atom® Processor E3815 (512K Cache, 1.46 GHz)



Downloads and Software







Need more help?

Contact support



All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Intel classifications are for informational purposes only and consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company as an importer and/or exporter is responsible for determining the correct classification of your transaction.

Refer to Datasheet for formal definitions of product properties and features.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

See http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html? wapkw=hyper+threading for more information including details on which processors support Intel® HT Technology.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers, typically represent 1,000-unit $purchase\ quantities, and\ are\ subject\ to\ change\ without\ notice.\ Taxes\ and\ shipping,\ etc.\ not\ included.\ Prices\ may\ vary\ for\ other\ package\ types\ and$ shipment quantities, and special promotional arrangements may apply. If sold in bulk, price represents individual unit. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

For benchmarking data see http://www.intel.com/performance.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different $processor families. See \ http://www.intel.com/content/www/us/en/processors/processor-numbers. html for \ details.$

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.



Company Information Our Commitment Communities Investor Relations Contact Us



Newsroom





Jobs





© Intel Corporation | Terms of Use | *Trademarks | Privacy | Cookies | Supply Chain Transparency | Site Map