Intel® Xeon® Processor D-1520 (6M Cache, 2.20 GHz)

- Essentials			
Status		Launched	
Launch Date		Q1'15	
Processor Number		D-1520	
Cache		6 MB	
Instruction Set		64-bit	
Instruction Set Extensions		AVX 2.0	
Embedded Options Available	Q	No	
Lithography		14 nm	
Recommended Customer Price		TRAY: \$199.00	
Datasheet		Link	
Conflict Free		Yes	
Scalability		1S Only	
Product Brief		Link	
- Performance			
# of Cores		4	
# of Threads		8	
Processor Base Frequency		2.2 GHz	
Max Turbo Frequency		2.6 GHz	
TDP	45 W		
- Memory Specifications			
Max Memory Size (dependent on memory type)		128 GB	
Memory Types		DDR4	
Max # of Memory Channels		2	
ECC Memory Supported [‡]	Q	Yes	
- Graphics Specifications			
Processor Graphics ‡		None	
- Expansion Options			
PCI Express Revision		2.0/3.0	
PCI Express Configurations [‡]		x4 x8 x16	
Max # of PCI Express Lanes		32	

10.0			
- I/O Specifications		I	
JSB Revision		2.0/3.0	
# of USB Ports		8	
Total # of SATA Ports		6	
Integrated LAN		Yes	
General Purpose IO		Yes	
UART		Yes	
- Package Specifications			
Max CPU Configuration		1	
T _{CASE}		80°C	
Package Size	Package Size		
Sockets Supported	Sockets Supported		
Low Halogen Options Available		See MDDS	
- Advanced Technologies			
Intel® Turbo Boost Technology ‡		2.0	
Intel® Hyper-Threading Technology ‡	Q	Yes	
Intel® Virtualization Technology (VT-x) ‡		Yes	
Intel® Virtualization Technology for Directed I/O (VT-d) [‡]	Q	Yes	
Intel® VT-x with Extended Page Tables (EPT) ‡	Q	Yes	
Intel® TSX-NI		Yes	
Intel® 64 [‡]	Q	Yes	
Idle States		Yes	
Enhanced Intel SpeedStep® Technology	Q	Yes	
Thermal Monitoring Technologies		Yes	
Intol® Data Protection Technology			
- Intel® Data Protection Technology	Q	Ven	
Intel® AES New Instructions Secure Key	Ч	Yes	
- Intel® Platform Protection Technology			
Trusted Execution Technology ‡	Q	Yes	
Execute Disable Bit ‡		Yes	
OS Guard		Yes	
- Networking Specifications			
SFI Interface		No	
KR Interface		No	
KR4 Interface		No	

KX Interface	No
KX4 Interface	No
100Base-T	No
1000Base-T	No
10GBase-T	Yes

Ordering and Spec Information

Trade Compliance Information

ECCN	CCATS	US HTS
5A992CN3	G071701++	8542310000

Ordering and Spec Information

Spec Code	Ordering Code	Step	RCP
Intel® Xeon® Processor D-15	20 (6M Cache, 2.20 GHz) FC-BGA14C, Tray		
SR29B	GG8067401741800	V1	\$199.00

Download Drivers

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter of record, and as such, your company is responsible for determining the correct classification of any item at the time of export.

Refer to Datasheet for formal definitions of product properties and features.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

"Conflict free" and "conflict-free" means "DRC conflict free", which is defined by the U.S. Securities and Exchange Commission rules to mean products that do not contain conflict minerals (tin, tantalum, tungsten and/or gold) that directly or indirectly finance or benefit armed groups in the Democratic Republic of the Congo (DRC) or adjoining countries. Intel also uses the term "conflict-free" in a broader sense to refer to suppliers, supply chains, smelters and refiners whose sources of conflict minerals do not finance conflict in the DRC or adjoining countries. Intel processors manufactured before January 1, 2013 are not conflict free. The conflict free designation refers only to product manufactured after that date. For Intel Boxed Processors, the conflict free designation refers to the processor only, not to any additional included accessories, such as heatsinks/coolers.

See http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html?wapkw=hyper+threading for more information including details on which processors support Intel® HT Technology.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers, typically represent 1,000-unit purchase quantities, and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. If sold in bulk, price represents individual unit. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

For benchmarking data see http://www.intel.com/performance.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See http://www.intel.com/content/www/us/en/processors/processor-numbers.html for details.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.

Send us your feedback!