



Intel® Xeon® Processor D-1518 (6M Cache, 2.20 GHz)

Specifications

- Essentials

Status	Launched
Launch Date	Q4'15
Processor Number	D-1518
Cache	6 MB
Instruction Set	64-bit
Instruction Set Extensions	AVX 2.0
Embedded Options Available	 Yes
Lithography	14 nm
Recommended Customer Price	TRAY: \$234.00
Datasheet	Link
Conflict Free	Yes
Scalability	1S Only
Product Brief	Link

- Performance

# of Cores	4
# of Threads	8
Processor Base Frequency	2.2 GHz
Max Turbo Frequency	2.2 GHz
TDP	35 W

- Memory Specifications

Max Memory Size (dependent on memory type)	128 GB
Memory Types	DDR4, DDR3
Max # of Memory Channels	2
ECC Memory Supported †	 Yes

- Graphics Specifications

Processor Graphics †	None
----------------------	------

- Expansion Options

PCI Express Revision	2.0/3.0
PCI Express Configurations †	x4 x8 x16
Max # of PCI Express Lanes	32

- I/O Specifications

USB Revision	2.0/3.0
# of USB Ports	8
Total # of SATA Ports	6
Integrated LAN	Yes
General Purpose IO	Yes
UART	Yes

- Package Specifications

Max CPU Configuration	1
Package Size	37.5mm x 37.5mm
Sockets Supported	FCBGA1667
Low Halogen Options Available	See MDDS

- Advanced Technologies

Intel® Turbo Boost Technology ‡	No
Intel® Hyper-Threading Technology ‡	Yes
Intel® Virtualization Technology (VT-x) ‡	Yes
Intel® Virtualization Technology for Directed I/O (VT-d) ‡	Yes
Intel® VT-x with Extended Page Tables (EPT) ‡	Yes
Intel® TSX-NI	Yes
Intel® 64 ‡	Yes
Idle States	Yes
Enhanced Intel SpeedStep® Technology	Yes
Thermal Monitoring Technologies	Yes

- Intel® Data Protection Technology

Intel® AES New Instructions	Yes
Secure Key	Yes

- Intel® Platform Protection Technology

Trusted Execution Technology ‡	Yes
Execute Disable Bit ‡	Yes
OS Guard	Yes

- Networking Specifications

SFI Interface	Yes
KR Interface	No
KR4 Interface	No
KX Interface	Yes

KX4 Interface	No
100Base-T	No
1000Base-T	Yes
10GBase-T	Yes

Ordering and Spec Information

Trade Compliance Information

ECCN	CCATS	US HTS
5A992CN3	G071701++	8542310000

Ordering and Spec Information

Spec Code	Ordering Code	Step	RCP
Intel® Xeon® Processor D-1518 (6M Cache, 2.20 GHz) FC-BGA14C, Tray			
SR2DN	GG8067402569700	V2	\$234.00

Download Drivers

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter of record, and as such, your company is responsible for determining the correct classification of any item at the time of export.

Refer to Datasheet for formal definitions of product properties and features.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

"Conflict free" and "conflict-free" means "DRC conflict free", which is defined by the U.S. Securities and Exchange Commission rules to mean products that do not contain conflict minerals (tin, tantalum, tungsten and/or gold) that directly or indirectly finance or benefit armed groups in the Democratic Republic of the Congo (DRC) or adjoining countries. Intel also uses the term "conflict-free" in a broader sense to refer to suppliers, supply chains, smelters and refiners whose sources of conflict minerals do not finance conflict in the DRC or adjoining countries. Intel processors manufactured before January 1, 2013 are not confirmed conflict free. The conflict free designation refers only to product manufactured after that date. For Intel Boxed Processors, the conflict free designation refers to the processor only, not to any additional included accessories, such as heatsinks/coolers.

See <http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html?wapkw=hyper+threading> for more information including details on which processors support Intel® HT Technology.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers, typically represent 1,000-unit purchase quantities, and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. If sold in bulk, price represents individual unit. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

For benchmarking data see <http://www.intel.com/performance>.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See <http://www.intel.com/content/www/us/en/processors/processor-numbers.html> for details.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.

Send us your feedback!