



金 龙 机 电 股 份 有 限 公 司

JINLONG MACHINERY & ELECTRONICS CO., LTD.

www.jinlong-machinery.com

sales@jinlong-machinery.com

规 格 书

SPECIFICATION




客 户 信 息	客户名称/Customer	
	客户料号/Part No.	
	客户承认签章 Customer Approved Signatures	



文件编号/Spec No.	KOTL-B-774	
品名/Description	圆柱直流马达/Cylindrical DC motor	
型号/Part No.	Z7AL2B1692082	
设计/Designed	审核/Checked	批准/Approved
		
2012.05.22	2012.05.22	2009.05.22

规格书内容/Contents


1、适用范围/ General Scope	3/9
2、使用条件/ Operating Conditions	3/9
3、测定条件/ Measuring Conditions	3/9
4、机械要求/ Mechanical Specifications	3/9
5、性能特征/Performance and characteristics	4/9
6、可靠性/Reliability	5/9
7、要求/Requirements	6/9
8、使用时注意事项/ attentions	6/9
9、包装/Packaging	7/9
10、外形图/Outline Drawing	8/9
11、修改记录 / REVISION HISTORY	9/9

2012.05.22		说明书/Specification		编号/No KOTL-B-774		代码/code:0		3/9	
型号/Model				Z7AL2B1692082					
1. 适用范围/ General Scope 本说明书适用于圆筒式永磁直流电机 Z7AL2B1692082 型 This specification applies to cylindrical permanent-magnetic motors DC model Z7AL2B1692082									
2. 使用条件/Operating Conditions									
项目/Item			规格/Specifications			条件·备注/Conditions & Remarks			
2-1		额定电压 Rated voltage	3.0V DC						
2-2		额定负荷 Rated load	振子 Counterweight			见 10. 外形图 As specified in 10. Outline Drawing			
2-3		旋转方向 Rotation	C.W/C.C.W (clockwise or counter clockwise)						
2-4		马达位置 Motor position	全方位 All position						
2-5		使用电压范围 Operating voltage	2.2～3.6V DC						
2-6		使用环境 Operating environment	-30 ～ 60℃, 常 湿 /Ordinary Humidity:65±20%RH			无水气凝结 No condensation of moisture			
2-7		保存环境 Storage environment	-40 ～ 60℃, 常 湿 /Ordinary Humidity:65±20%RH			无水气凝结 No condensation of moisture			
3. 测定条件/Measuring Conditions									
项目/Item			规格/Specifications			条件·备注/ Conditions & Remarks			
3-1		温度 Temperature	20±2℃						
3-2		湿度 Humidity	(63%～67%) RH						
3-3		位置 Motor position	轴向水平 Motor shaft horizontal			将马达固定在试验台上 Lock the motor in a test fixture			
标准测试条件为温度 20℃, 湿度 65%。如无疑异, 也可在温度 5～35℃、湿度 45～85%的条件下测试。 马达测试时, 放置方向为轴向水平。/The measurement at 20℃ & 65%RH is standard. If the judgment is not questionable, recognize measurement at 5℃ to 35℃ & relative humidity 45% to 85%. Direction of motor is shaft horizontal.									
4. 机械要求/Mechanical Specifications									
项目/Item			规格/Specifications			条件·备注/ Conditions & Remarks			
4-1		结构 Configuration	见 10. 外形图 As specified in 10. Outline Drawing			Outline drawing No: Z7AL2B1692082			
4-2		外观 Appearance	不含有机机械损坏及不充分的浸蚀等。 There shall be no evidence of mechanical damage and shall not have inadequate corrosion and so on			目测 (容许范围根据样品外形) Visual examination(allowable extent is based on boundary sample)			
4-3		轴向间隙 Shaft end play	0.1mm～0.3mm						
4-4		振子固定力 Holding strength of vibration weight	49N (5kgf) Min						


2012.05.22		说明书/Specification		编号/No KOTL-B-774		代码/code:0		4/9	
5. 性能特征/Performance and characteristics									
项目/Item			规格/ Specifications			条件·备注/ Conditions & Remarks			
5-1		额定转速 Rated speed	12,000±2500 rpm			在额定电压和额定负载（振子）下。 At rated voltage and rated load (Counterweight).			
5-2		额定电流 Rated current	250 mA Max						
5-3		堵转电流 Stall current	680 mA Max			在额定电压下。 At rated voltage			
5-4		起动电压 Starting voltage	1.7V DC Max			在额定负载（振子）下电枢的任意位置。 At rated load (Counterweight) any position of rotor.			
5-5		绝缘电阻 Insulation resistance	1MΩ Min			在 100V 直流下，端子和机壳间 At DC 100V between Terminal and case.			
5-6		端子阻抗 Terminal resistance	5.5Ω (±20%)			在 20℃ 下 At 20℃			
5-7		机械噪音 Mechanical noise	50dB(A)Max						
		在额定电压、额定负载（振子）下 背景噪音：不大于 28dB.A 计权 测试仪器：B&k 夹具重量：700g At rated voltage and rated load (Counterweight). Back ground noise 28dB(A) Max Measuring instruments: B&k Weight of jig:700g  Fig. A  Fig. B  Fig. C							

2012.05.22		说明书/Specification			编号/No KOTL-B-774		代码/code:0		5/9		
6. 可靠性/Reliability											
项目/Item		规格/Specification						判定标准/Judgment			
6-1	寿命 Life time							在常温常湿下放置 2h 后，马达应符合项 7-1 的要求。 After 2 hours exposure in ordinary temperature and humidity, Motors shall be approved as specified in item 7-1.			
		位置 Position	电压 Volt	负荷 Load	温度 Temp	湿度 Humi	寿命 Life				
		轴水平 Horizon	Rated 额定	Weight 振子	20℃	65%	200,000 Cycles				
6-2	低温放置 Low temp exposure	温度 /Temperature: $-40\pm 2^{\circ}\text{C}$ 时间 /Time: 96h						在常温常湿下放置 2h 后，马达应符合项 7-2 的要求。 After 2 hours exposure in ordinary temperature and humidity, Motors shall be approved as specified in item 7-2.			
6-3	高温放置 High temp. Exposure	温度 /Temperature: $60\pm 2^{\circ}\text{C}$ 时间 /Time: 96h									
6-4	湿度放置 Humidity exposure	温度 /Temperature: $40\pm 2^{\circ}\text{C}$ 湿度 /Humidity: $90\sim 95\%\text{RH}$ 放置时间 / Exposure time: 96h 无水气凝结/No condensation of moisture									
6-5	振动 Vibration	全振幅 /Displacement : 1.5mm (p-p) 频率 /Frequency: 10 ~ 55Hz 加速度 /Acceleration: 22m/s^2 周期 /Period: 20min 完成 10~55~10Hz /20 Minutes log sweep10~55~10Hz 方向 /Direction: x, y, z 时间 /Time: 每个方向 2h /Each 2 hours						测试结果应符合项 7-2 的要求。 After the test motors shall be approved as specified in item 7-2.			
6-6	自然跌落 Free fall	试验状态/Test state:将马达固定在约 75 克（包括马达本身）的物体上，落向水泥地面。 Set the motor to the approximately 75g (include the motor) weight of block drop the motor on the concrete floor. 高度 /Height: 1.5m 方向 /Direction: 6 个面 / 6 faces 次数 /Number of times: 每个面 2 次 / Twice 2 each						测试结果应符合项 7-2 的要求。 After the test motors shall be approved as specified in item 7-2.			
6-7	热冲击 Heat shock test	试验循环 /Test cycle :20 cycles 						在常温常湿下放置 2h 后，马达应符合项 7-2 的要求。 After 2 hours exposure in ordinary temperature and humidity, Motors shall be approved as specified in item 7-2.			


(Z7AL2) 圆柱马达包装 Packaging drawing of Z7AL2 cylindrical motor



50PCS (1 tray) × 10



500PCS (1 bundle) × 6



包装试验要求

1. 标准

- (1) 整箱重量小于等于9kg的, 跌落高度设定为75cm.
- (2) 整箱重量大于9kg但小于等于23kg的, 跌落高度设定为60cm.

2. 试验方法:

跌落要求为六面三棱一角.

- (1) 六面: 先从最大两面跌, 然后是中间大小的两面, 最后跌最小的两面, 一共六次.
- (2) 三棱: 指任选三条同一角的棱, 跌落秩序: 最长棱, 中间长度, 最短的, 一共三次.
- (3) 一角: 指上一步三条棱所组成的角, 跌落一次.

3. 判定基准

经过跌落试验后, 产品外观、性能无不良.

Package Test Requirement:

1. Criteria

- (1) The weight of the whole carton less than 9kg, the dropping height is 75cm.
- (2) The weight of the whole carton more than 9kg and less than 23kg, the dropping height is 60cm.

2. Test Methods:

Dropping requirement is 6 faces, 3 arris, 1 angle.

- (1) 6 faces: First dropping with two biggest faces, then dropping with another two middle faces, at last dropping with two smallest faces, once per face, total 6 faces.
- (2) 3 arris: Choose any 3 arris which make up of the same the angle, the dropping sequence is the longest arris, middle arris, shortest arris. Total 3 times.
- (3) 1 angle: Point to the angle which is made up with the 3 arris in the above step. Dropping for 1 time.


3. Judgement Criterion

After drop test, no evidence of damage on the appearance and performance.

Remarks:

500PCS/CTN: 24cm × 17.5cm × 27.5cm
 1000PCS/CTN: 34cm × 24cm × 27.5cm
 2000PCS/CTN: 47cm × 34cm × 27.5cm
 3000PCS/CTN: 51cm × 47cm × 27.5cm

OPP TAPE





10. 外形图/Outline Drawing

Z7AL2B1692082

技术要求/Technic requirement

1. 额定电压/Rated voltage: 3.0V
2. 额定电流/Rated current: 250mA Max
3. 额定转速/Rated speed: 12000 ± 2500rpm
4. 堵转电流/Stall current: 680mA Max
5. 端子阻抗/Terminal resistance: 5.5Ω(±20%)
6. 起动电压/Starting voltage: 1.7V Max
7. 轴向间隙/Shaft end play: 0.1~0.3mm
8. 导线规格/Lead spec: AWG30 UL3302
9. 所有尺寸为A向压紧后的尺寸(不包括轴向间隙)
/Overall length is measured after counterweight
being pressed against body in direction A. (Shaft
end play is not included.)
10. 未注线性公差为/Unmarked tolerance: ± 0.1mm



借（通）用件登记

底图总号

簽 字

日期

						金龙机电股份有限公司									
标 记	处 数	分 区	更改文件号		签 名	日 期	外 形 图								
设 计	杨 兰	2013. 05. 22	标准化		徐 珍	2013. 05. 22						阶 段 标 记		重 量	比 例
校 对											5:1				
审 核	杨淮华	2013. 05. 22													
工 艺			批 准		黄剑辉	2013. 05. 22	共 页		第 页		Z7AL2B1692082				

2013. 05. 22

规格书/Specification

编号/NO. K0TL-B-774

代码/code:0

8/9

