


Capacitor, ceramic, 470 pF, +/-5% Tol, 50V, X7R, 0805



Specifications

Termination Type:

Dissipation Factor:

Package Kind:

Package Size:

Package Type:

Package Quantity:

Insulation Resistance: Dielectric Strength:

Miscellaneous Electrical:

Marked:

Tin

No

2.5% 100 GOhm

125V

T&R

7in

4000

Paper Tape

Note: Kemet 50 Volt parts may be operated afor 63 volt applications

Dimensions (mm)

ID	Dimension	Tolerance	Manufacturer:	KEMET
L	2.00	+/-0.20	Capacitance:	470 pF
w	1.25	+/-0.20	Chip Size:	0805
т	0.78	+/-0.1	Voltage:	50V
В	0.50	+/-0.25	Temperature Coefficient:	X7R
S	0.75	min	Tolerance:	+/-5%
			Application:	Std Chip



© 2006-2012 IntelliData.net

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.