KEMET Part Number: EFA(005)-240X50M (UFSEFA005CT000, EFA(005)240X50M)



KEMET, EFA, Flex Suppressors, Noise Suppression



| General Information | |
|---------------------|--|
| Series: | EFA |
| Style: | Sheet |
| Description: | Flex Suppressor Flame Retardant Type |
| Features: | Flame Retardant Type |
| RoHS: | Yes |
| Qualifications: | UL94 V-0, UL File No. E176124 |
| Environment: | RoHS Compliant, Halogen Free, PVC Free, Lead Free, Red Phosphorus Free |

| Dimensions | |
|------------|-------------|
| Sheet Size | 240mmx50M |
| L | 50000mm NOM |
| W | 240mm NOM |
| Т | 0.05mm NOM |

| Packaging Specifications | |
|--------------------------|------------------|
| Tape Description: | No Adhesive Tape |
| Weight: | 1.86 kg |

| Specifications | |
|------------------------|--------------|
| Temperature Range: | -40/+105°C |
| Magnetic Permeability: | 60 u At 3MHz |
| Effective Frequency: | 10 GHz MAX |
| Resistance: | 1 MOhms MIN |
| Specific Gravity: | 3.1 Atm TYP |
| Conductivity: | 1.3 W/m K |
| Tensile Strength: | 6.8 MPa |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

