

# Memory Module Specifications

## KSM24ED8/16ME

16GB 2Rx8 2G x 72-Bit PC4-2400

CL17 288-Pin DIMM

### DESCRIPTION

Kingston's KSM24ED8/16ME is a 2G x 72-bit (16GB) DDR4-2400 CL17 SDRAM (Synchronous DRAM), 2Rx8, ECC, memory module, based on eighteen 1G x 8-bit FBGA components. The SPD is programmed to JEDEC standard latency DDR4-2400 timing of 17-17-17 at 1.2V. Each 288-pin DIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

### FEATURES

- Power Supply: VDD = 1.2V Typical
- VDDQ = 1.2V Typical
- VPP = 2.5V Typical
- VDDSPD = 2.2V to 3.6V
- Nominal and dynamic on-die termination (ODT) for data, strobe, and mask signals
- Low-power auto self refresh (LPASR)
- Data bus inversion (DBI) for data bus
- On-die VREFDQ generation and calibration
- Dual-rank
- On-board I2 serial presence-detect (SPD) EEPROM
- Temperature sensor with integrated SPD
- 16 internal banks; 4 groups of 4 banks each
- Fixed burst chop (BC) of 4 and burst length (BL) of 8 via the mode register set (MRS)
- Selectable BC4 or BL8 on-the-fly (OTF)
- Fly-by topology
- Terminated control command and address bus
- PCB: Height 1.23" (31.25mm)
- RoHS Compliant and Halogen-Free

### SPECIFICATIONS

CL(IDD)	17 cycles
Row Cycle Time (tRCmin)	46.16ns(min.)
Refresh to Active/Refresh Command Time (tRFCmin)	350ns(min.)
Row Active Time (tRASmin)	32ns(min.)
Maximum Operating Power	*
UL Rating	94 V - 0
Operating Temperature	0° C to +85° C
Storage Temperature	-55° C to +100° C

\*See IDD Specifications (page 2)

### Module Assembly




DRAM: MICRON (E-DIE)
----------------------

Continued >>

## IDD Specifications

Symbol	2400	Units
I <sub>DD0</sub>	657	mA
I <sub>PP0</sub>	54	mA
I <sub>DD1</sub>	765	mA
I <sub>DD2N</sub>	612	mA
I <sub>DD2NT</sub>	675	mA
I <sub>DD2P</sub>	450	mA
I <sub>DD2Q</sub>	540	mA
I <sub>DD3N</sub>	864	mA
I <sub>PP3N</sub>	54	mA
I <sub>DD3P</sub>	666	mA
I <sub>DD4R</sub>	1530	mA
I <sub>DD4W</sub>	1377	mA
I <sub>DD5R</sub>	747	mA
I <sub>PP5R</sub>	72	mA
I <sub>DD6N</sub>	612	mA
I <sub>DD6E</sub>	828	mA
I <sub>DD6R</sub>	378	mA
I <sub>DD6A</sub>	154.8	mA
I <sub>DD6A</sub>	378	mA
I <sub>DD6A</sub>	558	mA
I <sub>PP6X</sub>	90	mA
I <sub>DD7</sub>	1836	mA
I <sub>PP7</sub>	162	mA
I <sub>DD8</sub>	450	mA

## MODULE DIMENSIONS



The product images shown are for illustration purposes only and may not be an exact representation of the product. Kingston reserves the right to change any information at anytime without notice.