

Memory Module Specifications

KSM24SES8/8ME

8GB 1Rx8 1G x 72-Bit PC4-2400

CL17 260-Pin ECC SODIMM

DESCRIPTION

Kingston's KSM24SES8/8ME is a 1G x 72-bit (8GB) DDR4-2400 CL17 SDRAM (Synchronous DRAM) w/ parity, 1Rx8, ECC, memory module, based on nine 1G x 8-bit FBGA components. The SPD is programmed to JEDEC standard latency DDR4-2400 timing of 17-17-17 at 1.2V. Each 260-pin SODIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

FEATURES

- Power Supply: VDD = 1.2V
- VDDQ = 1.2V
- VPP = 2.5V
- VDDSPD = 2.20V to 3.60V
- Functionality and operations comply with the DDR4 SDRAM datasheet
- 16 internal banks
- Bank Grouping is applied, and CAS to CAS latency (tCCD_L, tCCD_S) for the banks in the same or different bank group accesses are available
- Data transfer rates: PC4-2400, PC4-2133, PC4-1866, PC4-1600
- Bi-Directional Differential Data Strobe
- 8 bit pre-fetch
- Burst Length (BL) switch on-the-fly BL8 or BC4(Burst Chop)
- Supports ECC error correction and detection
- On-Die Termination (ODT)
- Temperature sensor with integrated SPD
- This product is in compliance with the RoHS directive.
- Per DRAM Addressability is supported
- Internal Vref DQ level generation is available
- Write CRC is supported at all speed grades
- CA parity (Command/Address Parity) mode is supported
- RoHS Compliant and Halogen-Free

SPECIFICATIONS

CL(IDD)	17 cycles
Row Cycle Time (tRCmin)	46.16ns(min.)
Refresh to Active/Refresh Command Time (tRFCmin)	350ns(min.)
Row Active Time (tRASmin)	32ns(min.)
Maximum Operating Power	*
UL Rating	94 V - 0
Operating Temperature	0° C to +85° C
Storage Temperature	-55° C to +100° C

*See IDD Specifications (page 2)

Module Assembly





DRAM: MICRON (E-DIE)

Continued >>

IDD Specifications

Symbol	2400	Units
I _{DD0}	432	mA
I _{PP0}	27	mA
I _{DD1}	540	mA
I _{DD2N}	306	mA
I _{DD2NT}	450	mA
I _{DD2P}	225	mA
I _{DD2Q}	270	mA
I _{DD3N}	432	mA
I _{PP3N}	27	mA
I _{DD3P}	333	mA
I _{DD4R}	1305	mA
I _{DD4W}	1152	mA
I _{DD5R}	522	mA
I _{PP5R}	45	mA
I _{DD6N}	306	mA
I _{DD6E}	414	mA
I _{DD6R}	189	mA
I _{DD6A}	77.4	mA
I _{DD6A}	189	mA
I _{DD6A}	279	mA
I _{PP6X}	45	mA
I _{DD7}	1611	mA
I _{PP7}	135	mA
I _{DD8}	225	mA

MODULE DIMENSIONS



The product images shown are for illustration purposes only and may not be an exact representation of the product. Kingston reserves the right to change any information at anytime without notice.