

LENA-W

~45° wide beam

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 111.0 mm
Height	80 mm
Fastening	socket
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish	Coating
LENA-W	Reflector	PC	metal		lacquer

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C11980_LENA-W » Box size: 400 x 280 x 380 mm	60	60	60	4.0






PHOTOMETRIC DATA (MEASURED):



LED BXRA ES Rectangle
FWHM 46.0°
Efficiency 74 %
LEDs/each optic 1
Light colour White
Required components:
C12153_LENA-STD-BASE-BXRA
C11996_LENA-LENS




LED BXRA RS
FWHM 51.0°
Efficiency 76 %
LEDs/each optic 1
Light colour White
Required components:
C12229_LENA-STD-BASE-RS
C11996_LENA-LENS



LED BXRA RS
FWHM 51.0°
Efficiency 81 %
LEDs/each optic 1
Light colour White
Required components:
C12229_LENA-STD-BASE-RS





LED V10 Gen6
FWHM 39.0°
Efficiency 74 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13186_LENA-STD-BASE-CXA15
C11996_LENA-LENS




PHOTOMETRIC DATA (MEASURED):





LED Vero SE 29
FWHM 57.0°
Efficiency 86 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15083_LENA-STD-BASE-VERO29





LED VERO13
FWHM 48.0°
Efficiency 80 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS



LED VERO18
FWHM 52.0°
Efficiency 80 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS




LED VERO29
FWHM 57.0°
Efficiency 76 %
Peak intensity 1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
C11996_LENA-LENS



PHOTOMETRIC DATA (MEASURED):



CITIZEN

LED CL-L340
FWHM 45.0°
Efficiency 75 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11995_LENA-STD-BASE-CL340
C11996_LENA-LENS





CITIZEN

LED CLL02x/CLU02x (LES10)
FWHM 45.0°
Efficiency 81 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS
Bender Wirth: 434 Typ L1





CITIZEN

LED CLL03x/CLU03x
FWHM 47.0°
Efficiency 80 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENA-STD-BASE-CLL030
C11996_LENA-LENS



CITIZEN



LED CLL03x/CLU03x
FWHM 47.0°
Efficiency 81 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS
Bender Wirth: 433 Typ L1



PHOTOMETRIC DATA (MEASURED):



CITIZEN

LED CLL03x/CLU03x
FWHM 45.0°
Efficiency 79 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11996_LENA-LENS
A.A.G. STUCCHI: 8101/G2 + S-8000/11





CITIZEN

LED CLL03x/CLU03x
FWHM 47.0°
Efficiency 85 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENA-STD-BASE-CLL030




CITIZEN

LED CLL04x/CLU04x
FWHM 50.0°
Efficiency 81 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
IDEAL: 50-2204CT + 50-2100LN



CITIZEN



LED CLL04x/CLU04x
FWHM 52.0°
Efficiency 86 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENA-STD-BASE-CLL040



PHOTOMETRIC DATA (MEASURED):


CITIZEN

LED CLL04x/CLU04x
FWHM 50.0°
Efficiency 73 %
Peak intensity 1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11996_LENA-LENS
A.A.G. STUCCHI: 8102/G2 + S-8000/12





CITIZEN

LED CLL04x/CLU04x
FWHM 46.0°
Efficiency 76 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENA-STD-BASE-CLL040
C11996_LENA-LENS





CITIZEN

LED CLL04x/CLU04x
FWHM 49.0°
Efficiency 77 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11996_LENA-LENS
IDEAL: 50-2204CT + 50-2100LN



CITIZEN



LED CLU700/701/702
FWHM 39.0°
Efficiency 81 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS
Bender Wirth: 434 Typ L1



PHOTOMETRIC DATA (MEASURED):



CITIZEN

LED CLU720/721
FWHM 44.0°
Efficiency 81 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENA-STD-BASE-CLL030





CITIZEN

LED CLU720/721
FWHM 46.0°
Efficiency 76 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENA-STD-BASE-CLL030
C11996_LENA-LENS





CREE

LED CMA1840
FWHM 43.0°
Efficiency 86 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14146_LENA-STD-BASE-CXA18



CREE



LED CMA2550
FWHM 49.0°
Efficiency 86 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13324_LENA-STD-BASE-CXA25




PHOTOMETRIC DATA (MEASURED):





LED CMT14xx
FWHM 44.0°
Efficiency 85 %
Peak intensity 1.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
Bender Wirth: 434 Typ L1





LED CMT19xx
FWHM 47.0°
Efficiency 86 %
Peak intensity 1.6 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
Bender Wirth: 477 Typ L1



LED CMT28xx
FWHM 54.0°
Efficiency 85 %
Peak intensity 1.4 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
Bender Wirth: 471 Typ L3




LED CMT28xx
FWHM 51.0°
Efficiency 86 %
Peak intensity 1.5 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C12692_LENA-STD-BASE-CLL040





PHOTOMETRIC DATA (MEASURED):





LED CXA/B 15xx
 FWHM 38.0°
 Efficiency 77 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13186_LENA-STD-BASE-CXA15
 C11996_LENA-LENS





LED CXA/B 15xx
 FWHM 44.0°
 Efficiency 81 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENA-STD-BASE-VERO13-18
 C11996_LENA-LENS
 Bender Wirth: 441 Typ L1



LED CXA/B 1830
 FWHM 49.0°
 Efficiency 82 %
 Peak intensity 1.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENA-STD-BASE-VERO13-18
 C14169_LENA-CLEAR-LENS
 Bender Wirth: 437 Typ L1





LED CXA/B 1830
 FWHM 17.0°
 Efficiency 74 %
 Peak intensity 2.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENA-STD-BASE-VERO13-18
 C12231_LENA-FRESNEL
 Bender Wirth: 437 Typ L1





PHOTOMETRIC DATA (MEASURED):




LED CXA/B 1830
FWHM 48.0°
Efficiency 87 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
Bender Wirth: 437 Typ L1




LED CXA/B 25xx
FWHM 44.0°
Efficiency 76 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13324_LENA-STD-BASE-CXA25
C11996_LENA-LENS



LED CXA/B 25xx
FWHM 44.0°
Efficiency 81 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13324_LENA-STD-BASE-CXA25



LED CXA2011
FWHM 42.0°
Efficiency 75 %
LEDs/each optic 1
Light colour White
Required components:
C12105_LENA-STD-BASE-CXA20
C11996_LENA-LENS



PHOTOMETRIC DATA (MEASURED):


EVERLIGHT

LED CHI3030 19W
FWHM 50.0°
Efficiency 81 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
C11996_LENA-LENS
Bender Wirth: 468 Typ L3




EVERLIGHT

LED CHI3030 29W
FWHM 53.0°
Efficiency 78 %
Peak intensity 1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
C11996_LENA-LENS
Bender Wirth: 468 Typ L3





LUMILEDS

LED LUXEON CoB 1204/1205
FWHM 44.0°
Efficiency 68 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENA-STD-BASE-MEZ
C11996_LENA-LENS



LUMILEDS



LED LUXEON CoB 1204HD
FWHM 40.0°
Efficiency 86 %
Peak intensity 2.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11981_LENA-STD-BASE-COB-L110





PHOTOMETRIC DATA (MEASURED):





LED LUXEON CoB 1205HD
FWHM 43.0°
Efficiency 85 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11981_LENA-STD-BASE-COB-L110





LED LUXEON CoB 1208
FWHM 46.0°
Efficiency 73 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENA-STD-BASE-MEZ



LED LUXEON CoB 1208
FWHM 46.0°
Efficiency 68 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENA-STD-BASE-MEZ
C11996_LENA-LENS





LED LUXEON CoB 1216/1812
FWHM 51.0°
Efficiency 86 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENA-STD-BASE-CLL040





PHOTOMETRIC DATA (MEASURED):





LED LUXEON CoB 1216/1812
FWHM 50.0°
Efficiency 75 %
Peak intensity 1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11996_LENA-LENS
A.A.G. STUCCHI: 8102/G2 + S-8000/12




LED LUXEON CoB 1216/1812
FWHM 50.0°
Efficiency 81 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENA-STD-BASE-CLL040
C11996_LENA-LENS



LED LUXEON CoB 1216/1812
FWHM 51.0°
Efficiency 79 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
A.A.G. STUCCHI: 8102/G2 + S-8000/12



LED LUXEON K12
FWHM 45.0°
Efficiency 74 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12924_LENA-STD-BASE-LUXEON-K
C11996_LENA-LENS





PHOTOMETRIC DATA (MEASURED):





LED LUXEON K16
FWHM 46.0°
Efficiency 72 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12924_LENA-STD-BASE-LUXEON-K
C11996_LENA-LENS





LED CDM-14 (Dim-To-Warm)
FWHM 47.0°
Efficiency 82 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS
Bender Wirth: 491 Typ L2



LED CDM-14 (Dim-To-Warm)
FWHM 47.0°
Efficiency 87 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
Bender Wirth: 491 Typ L2




LED CDM-18 (Dim-To-Warm)
FWHM 48.0°
Efficiency 82 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS
Bender Wirth: 491 Typ L2





PHOTOMETRIC DATA (MEASURED):




LED CDM-18 (Dim-To-Warm)
FWHM 50.0°
Efficiency 87 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
Bender Wirth: 491 Typ L2





LED CDM-9 (Dim-To-Warm)
FWHM 44.0°
Efficiency 87 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
Bender Wirth: 490 Typ L1



LED CDM-9 (Dim-To-Warm)
FWHM 44.0°
Efficiency 82 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS
Bender Wirth: 490 Typ L1





LED CTM-14 (Tunable White)
FWHM 46.0°
Efficiency 81 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
C12606_LENINA-DL
Bender Wirth: 442 Typ L3





PHOTOMETRIC DATA (MEASURED):





LED CTM-14 (Tunable White)
FWHM 45.0°
Efficiency 86 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
Bender Wirth: 442 Typ L3





LED CTM-18 (Tunable White)
FWHM 49.0°
Efficiency 81 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
C11996_LENA-LENS
Bender Wirth: 442 Typ L3



LED CTM-18 (Tunable White)
FWHM 49.0°
Efficiency 87 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
Bender Wirth: 442 Typ L3




LED CTM-22 (Tunable White)
FWHM 53.0°
Efficiency 81 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
C11996_LENA-LENS
Bender Wirth: 489 Typ L6





PHOTOMETRIC DATA (MEASURED):





LED CTM-22 (Tunable White)
FWHM 55.0°
Efficiency 86 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
Bender Wirth: 494 Typ L3





LED CxM-14 (19x19)
FWHM 48.0°
Efficiency 78 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENA-STD-BASE-CLL030
C11996_LENA-LENS



LED COB J-Type
FWHM 49.0°
Efficiency 79 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS
Bender Wirth: 463 Typ L2



LED COB L-Type (LES 11)
FWHM 46.0°
Efficiency 79 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS
Bender Wirth: 438 Typ L1



PHOTOMETRIC DATA (MEASURED):





LED COB L-Type (LES 9)
 FWHM 45.0°
 Efficiency 79 %
 Peak intensity 1.4 cd/lm
 LEDs/each optic 1
 Light colour White

Required components:

C13868_LENA-STD-BASE-VERO13-18

C11996_LENA-LENS

Bender Wirth: 438 Typ L1





LED NVCWJ024Z-V1MT: COB J-Type Tunable White
 FWHM 46.0°
 Efficiency 81 %
 Peak intensity 1.4 cd/lm
 LEDs/each optic 1
 Light colour White

Required components:

C13868_LENA-STD-BASE-VERO13-18

C11996_LENA-LENS

Bender Wirth: 498 Typ L2





LED NVCWJ024Z-V1MT: COB J-Type Tunable White
 FWHM 45.0°
 Efficiency 86 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White

Required components:

C13868_LENA-STD-BASE-VERO13-18

Bender Wirth: 498 Typ L2





LED Soleriq S13
 FWHM 47.0°
 Efficiency 78 %
 Peak intensity 1.4 cd/lm
 LEDs/each optic 1
 Light colour White

Required components:

C13868_LENA-STD-BASE-VERO13-18

C11996_LENA-LENS

Bender Wirth: 437 Typ L1





PHOTOMETRIC DATA (MEASURED):

OSRAM

Opto Semiconductors

LED Soleriq S19
FWHM 50.0°
Efficiency 78 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White



Required components:
C13867_LENA-STD-BASE-VERO29
C11996_LENA-LENS
Bender Wirth: 462 Typ L3



PHILIPS

LED Fortimo SLM L13 CoB
FWHM 44.0°
Efficiency 79 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White



Required components:
C12292_LENA-STD-BASE-MEZ
C11996_LENA-LENS



PHILIPS

LED Fortimo SLM L13 CoB
FWHM 44.0°
Efficiency 85 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White



Required components:
C12292_LENA-STD-BASE-MEZ



PHILIPS

LED Fortimo SLM L15 CoB
FWHM 46.0°
Efficiency 79 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White



Required components:
C12292_LENA-STD-BASE-MEZ
C11996_LENA-LENS



PHOTOMETRIC DATA (MEASURED):



PHILIPS

LED Fortimo SLM L15 CoB
FWHM 47.0°
Efficiency 85 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12292_LENA-STD-BASE-MEZ





PHILIPS

LED Fortimo SLM L19 CoB
FWHM 50.0°
Efficiency 85 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENA-STD-BASE-CLL040





PHILIPS

LED Fortimo SLM L19 CoB
FWHM 48.0°
Efficiency 79 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENA-STD-BASE-CLL040
C11996_LENA-LENS



PHILIPS



LED Fortimo SLM L23 CoB
FWHM 51.0°
Efficiency 85 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENA-STD-BASE-CLL040



PHOTOMETRIC DATA (MEASURED):



PHILIPS

LED Fortimo SLM L23 CoB
 FWHM 50.0°
 Efficiency 79 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12692_LENA-STD-BASE-CLL040
 C11996_LENA-LENS





SAMSUNG

LED LC016D / LC019D / LC026D / LC033D
 FWHM 49.0°
 Efficiency 81 %
 Peak intensity 1.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12691_LENA-STD-BASE-CLL030
 C11996_LENA-LENS





SAMSUNG

LED LC040D / LC060D / LC080D
 FWHM 51.0°
 Efficiency 81 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12692_LENA-STD-BASE-CLL040
 C11996_LENA-LENS



LED ZC12/18
 FWHM 48.0°
 Efficiency 77 %
 Peak intensity 1.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12691_LENA-STD-BASE-CLL030
 C11996_LENA-LENS



PHOTOMETRIC DATA (MEASURED):

SHARP



LED Mega Zenigata (GW5DGC)
FWHM 44.0°
Efficiency 75 %
LEDs/each optic 1
Light colour White
Required components:
C12292_LENA-STD-BASE-MEZ
C11996_LENA-LENS

SHARP

LED Mega Zenigata (GW5DGC)
FWHM 44.0°
Efficiency 80 %
LEDs/each optic 1
Light colour White
Required components:
C12292_LENA-STD-BASE-MEZ



TRIDONIC

LED SLE G7 LES15
FWHM 48.0°
Efficiency 88 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENA-STD-BASE-CLL030



TRIDONIC


LED SLE G7 LES17 H
FWHM 49.0°
Efficiency 86 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14547_LENA-ADAPTER-B



PHOTOMETRIC DATA (MEASURED):



TRIDONIC

LED SLE G7 LES21 H
FWHM 52.0°
Efficiency 86 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14547_LENA-ADAPTER-B



XICATO


LED XOB 14.5 mm
FWHM 46.0°
Efficiency 89 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12691_LENA-STD-BASE-CLL030




PHOTOMETRIC DATA (SIMULATED):




LED V10 Gen7
FWHM 44.0°
Efficiency 81 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C13868_LENA-STD-BASE-VERO13-18
 C11996_LENA-LENS
 Bender Wirth: 486 Typ L1




LED V10 Gen7
FWHM 46.0°
Efficiency 88 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C13868_LENA-STD-BASE-VERO13-18
 Bender Wirth: 486 Typ L1



LED V13 Gen7
FWHM 47.0°
Efficiency 82 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C13868_LENA-STD-BASE-VERO13-18
 C11996_LENA-LENS
 Bender Wirth: 477 Typ L1




LED V13 Gen7
FWHM 44.0°
Efficiency 87 %
Peak intensity 1.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 IDEAL: 50-2103CT + 50-2100LN




PHOTOMETRIC DATA (SIMULATED):




LED V13 Gen7
FWHM 42.0°
Efficiency 85 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11996_LENA-LENS
IDEAL: 50-2103CT + 50-2100LN




LED V22 Gen7
FWHM 51.0°
Efficiency 87 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
C11996_LENA-LENS
Bender Wirth: 431 Typ L3



LED V22 Gen7
FWHM 51.0°
Efficiency 87 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13867_LENA-STD-BASE-VERO29
Bender Wirth: 431 Typ L3




LED CXA/B 30xx
FWHM 42.0°
Efficiency 86 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
IDEAL: 50-2234C + 50-2100LN



PHOTOMETRIC DATA (SIMULATED):



LED CXA/B 30xx
FWHM 43.0°
Efficiency 81 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C11996_LENA-LENS
IDEAL: 50-2234C + 50-2100LN




LED CxM-14 (19x19)
FWHM 47.0°
Efficiency 86 %
Peak intensity 1.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
Bender Wirth: 433 Typ L1



LED CxM-14 (19x19)
FWHM 47.0°
Efficiency 81 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C13868_LENA-STD-BASE-VERO13-18
C11996_LENA-LENS
Bender Wirth: 433 Typ L1



LED CxM-22 (28x28)
FWHM 48.0°
Efficiency 83 %
Peak intensity 1.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C12692_LENA-STD-BASE-CLL040



PHOTOMETRIC DATA (SIMULATED):




LED CxM-9 (13.5x13.5)
 FWHM 44.0°
 Efficiency 86 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENA-STD-BASE-VERO13-18
 Bender Wirth: 434 Typ L1



LED CxM-9 (13.5x13.5)
 FWHM 45.0°
 Efficiency 81 %
 Peak intensity 1.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENA-STD-BASE-VERO13-18
 C11996_LENA-LENS
 Bender Wirth: 434 Typ L1





LED Soleriq S15
 FWHM 48.0°
 Efficiency 88 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C12691_LENA-STD-BASE-CLL030




LED ZC12/18
 FWHM 47.0°
 Efficiency 86 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C13868_LENA-STD-BASE-VERO13-18
 Bender Wirth: 433 Typ L1

PHOTOMETRIC DATA (SIMULATED):

 SEOUL SEMICONDUCTOR	
LED	ZC12/18
FWHM	47.0°
Efficiency	81 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C13868_LENA-STD-BASE-VERO13-18	
C11996_LENA-LENS	
Bender Wirth: 433 Typ L1	

 SEOUL SEMICONDUCTOR	
LED	ZC4/6
FWHM	44.0°
Efficiency	86 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C13868_LENA-STD-BASE-VERO13-18	
Bender Wirth: 434 Typ L1	

 SEOUL SEMICONDUCTOR	
LED	ZC4/6
FWHM	45.0°
Efficiency	81 %
Peak intensity	1.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C13868_LENA-STD-BASE-VERO13-18	
C11996_LENA-LENS	
Bender Wirth: 434 Typ L1	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)