

## LENA-STD-BASE-VERO29

Basepart for LENA and LENINA reflectors. Compatible with Bridgelux VERO29 and VERO29-SE.

#### **TECHNICAL SPECIFICATIONS:**

Dimensions Ø 67.0 mm

Height 11.6 mm

Fastening screw

ROHS compliant yes 🛈

### **MATERIAL SPECIFICATIONS:**

Component LENA-STD-BASE-VEF

# Туре



Colour

Finish

LENA-STD-BASE-VERO29	Base part	PBT		white	
ORDERING INFORMATION:					
Component		Qty in box	MOQ	MPQ	Box weight (kg)
C15083_LENA-STD-BASE-VERO29		120	60	60	1.0


Material

#### Component

C15083\_LENA-STD-BASE-VERO29 » Box size: 273 x 183 x 135 mm

Last update: 07/12/2019	Subject to change without prior notice	Published: 2	1/05/2018
LEDiL is a registered trademark of LEDiL	. Oy in the European Union, USA, and certain other cou	untries.	1/3







#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

#### Local sales and technical support www.ledil.com/ where\_to\_buy

Shipping locations Salo, Finland Hong Kong, China

Distribution Partners www.ledil.com/ where\_to\_buy