

TINA2-RS

~14° spot beam optimized for CREE XP-E.
Assembly with holder and installation tape.

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 16.1 mm
Height	9.7 mm
Fastening	tape
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
TINA2-RS	Single lens	PMMA	clear	
TINA2-XP-HLD-TAPE-BLK	Holder	PC	black	
TINA-TAPE3	Tape	PU tape	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA11016_TINA2-RS	Single lens	4140	230	230	8.1
» Box size: 451 x 241 x 298 mm					








PHOTOMETRIC DATA (MEASURED):




LED XP-E
FWHM 11.0°
Efficiency 90 %
Peak intensity 17.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XP-E2
FWHM 11.0°
Efficiency 89 %
Peak intensity 16.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-G
FWHM 15.0°
Efficiency 93 %
Peak intensity 9 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XP-G2
FWHM 15.0°
Efficiency 91 %
Peak intensity 10 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



LG Innotek

LED H35B0 (LEMWA32)
FWHM 14.0°
Efficiency 91 %
Peak intensity 11 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LG Innotek

LED H35C0 (LEMWA33)
FWHM 16.0°
Efficiency 91 %
Peak intensity 8 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LG Innotek

LED H35C1 (LEMWA33)
FWHM 16.0°
Efficiency 88 %
Peak intensity 8.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHILIPS


LED Fortimo FastFlex 2x8 DS G3
FWHM 15.0°
Efficiency 86 %
Peak intensity 9.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):



LED XP-G2 HE
FWHM 18.0°
Efficiency 80 %
Peak intensity 6.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED SFH 4170S
FWHM 8.5°
Efficiency 78 %
LEDs/each optic 1
Light colour White
Required components:



SEOUL SEMICONDUCTOR

LED Z5
FWHM 8.0°
Efficiency 91 %
Peak intensity 31.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salu, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)