

OLGA-WAS

Asymmetric beam for wall-washing. Assembly with holder and installation tape.

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 32.0 mm
Height	20.8 mm
Fastening	tape
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
OLGA-WAS	Single lens	PMMA	clear	
OLGA-HLD	Holder	PC	black	
SPUTNIK-TAPE3	Tape	PU tape	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA16308_OLGA-WAS	Single lens	792	132	66	9.0
» Box size: 476 x 273 x 292 mm					









PHOTOMETRIC DATA (MEASURED):




LED XHP35 HD
FWHM Asymmetric
Efficiency 73 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XHP35 HI
FWHM Asymmetric
Efficiency 76 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XHP50.2
FWHM Asymmetric
Efficiency 67 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XHP70.2
FWHM Asymmetric
Efficiency 70 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):




LED XP-E2
FWHM Asymmetric
Efficiency 76 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XP-G2
FWHM Asymmetric
Efficiency 75 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-G2
FWHM Asymmetric
Efficiency 76 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XP-G3
FWHM Asymmetric
Efficiency 72 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):




LED XP-L2
FWHM Asymmetric
Efficiency 72 %
Peak intensity 1 cd/Im
LEDs/each optic 1
Light colour White
Required components:





LED XQ-E HD
FWHM Asymmetric
Efficiency 67 %
Peak intensity 1.1 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED XQ-E HI
FWHM Asymmetric
Efficiency 72 %
Peak intensity 1.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:





LED XT-E
FWHM Asymmetric
Efficiency 71 %
Peak intensity 1.1 cd/Im
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



LUMILEDS

LED LUXEON 5050 Round LES
FWHM Asymmetric
Efficiency 75 %
Peak intensity 1 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LUMILEDS

LED LUXEON M/MX
FWHM Asymmetric
Efficiency 75 %
Peak intensity 0.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:





LUMILEDS

LED LUXEON MZ
FWHM Asymmetric
Efficiency 75 %
Peak intensity 1.1 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LUMILEDS



LED LUXEON TX
FWHM Asymmetric
Efficiency 72 %
Peak intensity 1.2 cd/Im
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



LUMILEDS

LED LUXEON V
FWHM Asymmetric
Efficiency 73 %
Peak intensity 1 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LUMILEDS

LED LUXEON Z ES
FWHM Asymmetric
Efficiency 76 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:




NICHIA

LED NCSxE17A
FWHM Asymmetric
Efficiency 72 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:



NICHIA


LED NVSW319B
FWHM Asymmetric
Efficiency 75 %
Peak intensity 1 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):




LED NVSxE21A
FWHM Asymmetric
Efficiency 72 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NVSxx19B/NVSxx19C
FWHM Asymmetric
Efficiency 75 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED Duris S8
FWHM Asymmetric
Efficiency 75 %
Peak intensity 0.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED OSCONIQ P 3737 (2W version)
FWHM Asymmetric
Efficiency 75 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):


OSRAM
Opto Semiconductors

LED OSCONIQ P 3737 (3W version)
FWHM Asymmetric
Efficiency 75 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OSRAM
Opto Semiconductors

LED OSLON Square CSSRM2/CSSRM3
FWHM Asymmetric
Efficiency 76 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OSRAM
Opto Semiconductors

LED OSLON SSL 150
FWHM Asymmetric
Efficiency 71 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM
Opto Semiconductors


LED OSTAR Stage (S2WN)
FWHM Asymmetric
Efficiency 76 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour RGBW
Required components:



PHOTOMETRIC DATA (MEASURED):


SAMSUNG

LED LH231B
FWHM Asymmetric
Efficiency 74 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SAMSUNG

LED LH351B
FWHM Asymmetric
Efficiency 78 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SAMSUNG

LED LH351C
FWHM Asymmetric
Efficiency 79 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SAMSUNG


LED LH351D
FWHM Asymmetric
Efficiency 77 %
Peak intensity 1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LH508A
FWHM Asymmetric
Efficiency 75 %
Peak intensity 1 cd/Im
LEDs/each optic 1
Light colour White
Required components:



SEOUL SEMICONDUCTOR


LED Z5M3
FWHM Asymmetric
Efficiency 71 %
Peak intensity 1.1 cd/Im
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED XP-G2 HE
FWHM Asymmetric
Efficiency 79 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NV4WB35AM
FWHM Asymmetric
Efficiency 78 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NV4x144A
FWHM Asymmetric
Efficiency 78 %
Peak intensity 0.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)