


## FLORENTINA-1-M


~30° medium beam

### TECHNICAL SPECIFICATIONS:

Dimensions	39.7 mm
Height	13 mm
Fastening	tape
ROHS compliant	yes 


### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
ROSE-CMC-M	Single lens	PC	clear	
FLORENTINA-1-HLD	Holder	PC	black	
ROSE-TAPE	Tape	PU tape	black	



### ORDERING INFORMATION:



Component		Qty in box	MOQ	MPQ	Box weight (kg)
FCA15451_FLORENTINA-1-M	Single lens	840		60	7.9
» Box size: 480 x 280 x 300 mm					





#### PHOTOMETRIC DATA (MEASURED):





LED Bridgelux SMD 5050  
 FWHM 32.0°  
 Efficiency 76 %  
 Peak intensity 2.2 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60





LED XHP35 HD  
 FWHM 32.0°  
 Efficiency 76 %  
 Peak intensity 2.2 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60



LED XHP35 HI  
 FWHM 31.0°  
 Efficiency 77 %  
 Peak intensity 2.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED XP-G2  
 FWHM 31.0°  
 Efficiency 78 %  
 Peak intensity 2.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60





#### PHOTOMETRIC DATA (MEASURED):





LED XP-L HD  
 FWHM 31.0°  
 Efficiency 76 %  
 Peak intensity 2.3 cd/Im  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60





LED XP-L2  
 FWHM 32.0°  
 Efficiency 74 %  
 Peak intensity 2.2 cd/Im  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60



LED XT-E  
 FWHM 31.0°  
 Efficiency 76 %  
 Peak intensity 2.5 cd/Im  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60



LED LG 5630  
 FWHM 31.0°  
 Efficiency 82 %  
 Peak intensity 2.6 cd/Im  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C16701\_FLORENTINA-1-SHD-60-WHT









#### PHOTOMETRIC DATA (MEASURED):





LED LG 5630  
FWHM 31.0°  
Efficiency 80 %  
Peak intensity 2.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
C15427\_FLORENTINA-1-SHD-60





LED LUXEON 3030 2D (Round LES)  
FWHM 31.0°  
Efficiency 80 %  
Peak intensity 2.8 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED LUXEON 5050 Round LES  
FWHM 31.0°  
Efficiency 77 %  
Peak intensity 2.3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
C15427\_FLORENTINA-1-SHD-60





LED LUXEON TX  
FWHM 31.0°  
Efficiency 77 %  
Peak intensity 2.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
C15427\_FLORENTINA-1-SHD-60





#### PHOTOMETRIC DATA (MEASURED):





LED NF2x757G  
 FWHM 31.0°  
 Efficiency 82 %  
 Peak intensity 2.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C16701\_FLORENTINA-1-SHD-60-WHT





LED NF2x757G  
 FWHM 31.0°  
 Efficiency 81 %  
 Peak intensity 2.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60



LED NVSW319B  
 FWHM 31.0°  
 Efficiency 79 %  
 Peak intensity 2.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60



LED NVSxx19B/NVSxx19C  
 FWHM 31.0°  
 Efficiency 78 %  
 Peak intensity 2.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:  
 C15427\_FLORENTINA-1-SHD-60





#### PHOTOMETRIC DATA (MEASURED):

##### OSRAM

Opto Semiconductors



LED OSLON Square CSSRM2/CSSRM3  
FWHM 31.0°  
Efficiency 79 %  
Peak intensity 2.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
C15427\_FLORENTINA-1-SHD-60



##### OSRAM

Opto Semiconductors



LED OSLON Square EC  
FWHM 31.0°  
Efficiency 78 %  
Peak intensity 2.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
C15427\_FLORENTINA-1-SHD-60



##### OSRAM



Opto Semiconductors

LED OSLON SSL 150  
FWHM 31.0°  
Efficiency 78 %  
Peak intensity 2.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
C15427\_FLORENTINA-1-SHD-60









##### SAMSUNG

LED LM561B  
FWHM 31.0°  
Efficiency 80 %  
Peak intensity 2.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:  
C15427\_FLORENTINA-1-SHD-60




### PHOTOMETRIC DATA (MEASURED):

 SEOUL SEMICONDUCTOR	<p>LED                    SEOUL 5630</p> <p>FWHM                31.0°</p> <p>Efficiency            83 %</p> <p>Peak intensity       2.8 cd/lm</p> <p>LEDs/each optic    1</p> <p>Light colour         White</p> <p>Required components:</p> <p>                         C15427_FLORENTINA-1-SHD-60</p>		
 SEOUL SEMICONDUCTOR	<p>LED                    Z8Y22P</p> <p>FWHM                30.0°</p> <p>Efficiency            74 %</p> <p>Peak intensity       2.4 cd/lm</p> <p>LEDs/each optic    1</p> <p>Light colour         White</p> <p>Required components:</p> <p>                         C15427_FLORENTINA-1-SHD-60</p>		

### PHOTOMETRIC DATA (SIMULATED):



LED	XP-G2 HE
FWHM	31.0°
Efficiency	86 %
Peak intensity	2.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	
C15427_FLORENTINA-1-SHD-60	





#### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)