

PRODUCT DATASHEET Leila series

last update 12/6/2013

Product number	FCN10804_LR1-RS		
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status	Leila Pack LUXEON Rebel White 21.6 mm 14.3 mm Round PMMA PC Glue On production	FWHM Efficiency cd/lm Gerber File	8 degrees 96 % (simulated) 0.000 Available
Product number	FCN11738_LR1-RS2		
Family Type LED Color Diameter Height Style	Leila Pack LUXEON Rebel White 21.6 mm 14.3 mm Round	FWHM Efficiency cd/Im Gerber File	10 degrees 93 % 16.000 Available
Optic Material Holder Material Fastening Status Product number	PMMA PC Glue On production FCN10806_LR1-D		
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status Product number	Leila Pack LUXEON Rebel White 21.6 mm 14.3 mm Round PMMA PC Glue On production FCN10803_LR1-M	FWHM Efficiency cd/Im Gerber File	11 degrees 96 % (simulated) 0.000 Available
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status	Leila Pack LUXEON Rebel White 21.6 mm 14.3 mm Round PMMA PC Glue On production	FWHM Efficiency cd/Im Gerber File	22 degrees 91 % (simulated) 0.000 Available

January 7th 2016 4:14 Copyright Ledil Oy - Subject to change without prior notice - Page 1/4

Ledil Oy Salorankatu 10 24240 SALO Finland



PRODUCT DATASHEET Leila series

last update 12/6/2013

	Product number	FCN11458_LR1-M2		
	Family	Leila	FWHM	30 degrees
	Туре	Pack	Efficiency	90 %
	LED	LUXEON Rebel	cd/lm	-
	Color	White	Gerber File	Available
	Diameter	21.6 mm		
11111111111111111111111111111111111111	Height	14.3 mm		
	Style	Round		
	Optic Material	PMMA		
	Holder Material	PC		
	Fastening	Glue		
	Status	On production		
	Product number	FCN10805_LR1-REC		
and a second second second	Family	Leila	FWHM	36+20 degrees
	Туре	Pack	Efficiency	92 %
	LED	LUXEON Rebel	cd/lm	(simulated) 0.000
and the second second	Color	White	Gerber File	Available
	Diameter	21.6 mm		
	Height	14.3 mm		
	Style	Round		
	Optic Material	PMMA		
	Holder Material	PC		
	Fastening	Glue		
	Status	On production		
	Product number	FCN11106_LR1-O-90		
	Family	Leila	FWHM	38+15.5 degrees
ATTACH AND A STATE OF	Туре	Pack	Efficiency	96 %
	LED	LUXEON Rebel	cd/lm	-
	Color	White	Gerber File	Available
	Diameter	21.6 mm		
	Height	14.3 mm		
	Style	Round		
	Optic Material	PMMA		
	Holder Material	PC		
	Fastening	Glue		
al	Status	On production		
	Product number	FCN10890_LR1-W		
	Family	Leila	FWHM	48 degrees
STATES -	Туре	Pack	Efficiency	94 %
	LED	LUXEON Rebel	cd/lm	(simulated) 0.000
	Color	White	Gerber File	Available
	Diameter	21.6 mm		
	Height	14.3 mm		
	Style	Round		
	Optic Material	PMMA		
	Holder Material	PC		
	Fastening	Glue		
	Status	On production		

January 7th 2016 4:14 Copyright Ledil Oy - Subject to change without prior notice - Page 2/4

Ledil Oy Salorankatu 10 24240 SALO Finland



NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.

Ledil Oy Salorankatu 10 24240 SALO Finland



PRODUCT DATASHEET Leila series last update 12/6/2013

GENERAL INFORMATION

- Product series especially designed & optimized for LUXEON Rebel series of LEDs.

- Special care taken to make light distribution as uniform as possible.

- Lens material optical grade PMMA with high UV and temperature resistance. Allows use of high current and temperature conditions.

Please find more information about used material from below:

http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20UL94_Yellow%20Card.pdf http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20PLEXIGLAS-Datasheet.pdf - Optic holder molded by high quality PC material (120 dergees of Celcius / 248 degrees of Fahrenheit).


- Fastening to PCB with appropriate adhesive. By clicking link below you can find Ledil recommended glue options.

http://www.ledil.com/datasheets/DataSheet_GLUES.pdf


NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit boar weaken the strength of the glue.

NOTE 2: All surfaces where glue is applied must be clean, dry and free from grease and dirt. If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer -this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.


Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.




Luminaire: Ledil Oy FA10804_LR1-RS FA10804_LR1-RS Lamps: 1 x LUXEON REBEL




Luminaire: Ledil OY FCN11738_LR1-RS2-RE LOR=93% Lamps: 1 x Luxeon Rebel 250mA 78Im




Luminaire: Ledil Oy FA10803_LR1-M FA10803_LR1-M Lamps: 1 x Luxeon Rebel




Luminaire: Ledil Oy FA10805_LR1-REC FA10805_LR1-REC Lamps: 1 x Luxeon Rebel (white)



Luminaire: Ledil Oy FA10890_LR1-W FA10890_LR1-W Lamps: 1 x Luxeon Rebel (white)




Luminaire: Ledil Oy FA10804_LR1-RS FA10804_LR1-RS Lamps: 1 x LUXEON REBEL




_____ C0 - C180 _____ C90 - C270

Luminaire: Ledil OY FCN11738_LR1-RS2-RE LOR=93% Lamps: 1 x Luxeon Rebel 250mA 78lm




Luminaire: Ledil Oy FA10803_LR1-M FA10803_LR1-M Lamps: 1 x Luxeon Rebel



_____ C0 - C180 _____ C90 - C270

Luminaire: Ledil Oy FA10805_LR1-REC FA10805_LR1-REC Lamps: 1 x Luxeon Rebel (white)



Luminaire: Ledil Oy FA10890_LR1-W FA10890_LR1-W Lamps: 1 x Luxeon Rebel (white)

