

## SUMMARY



Image is for illustrative purpose only

### # Wires

Low voltage 8

Series 2K

Termination type

IP rating 68

AWG wire size 22.00 - 22.00

Cable Ø 0.00 - 0.00 mm

Status active

### Download

[Request a quote](#)

[Catalog](#)

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model FT\*: T-plug with receptacles (straight & elbow)

Keying 1 key (alpha=0, plug: male contacts, receptacle: female contacts)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Weight 115.14 g

### Performance

Configuration 2K.308 : 8 Low Voltage

Insulator L: PEEK (UL 94 / V-0/1.5)

Rated Current 10 Amps

### Specifications

Contact Dia.: 0.9 mm (0.035in)

### Others

Endurance (Shell): 5000 mating cycles

Temp (min / max): -55°C / +200°C

Humidity (max): <=95% [at 60 deg C / 140 F]

Vibration: 15 g [10 Hz - 2000 Hz]

Shock Resistance: 100 g [ 6 ms]


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Climatical Category: 50/175/21  
Shielding (min): 95 dB (10 MHz)  
Shielding (min): 80 dB (1 GHz)  
Salt Spray Corrosion: >1000 hr

---

## DRAWINGS

### Draws



### Dimensions

	A	B	H	L	M
mm.	16	19	48	77	60
in.	0.63	0.75	1.89	3.03	2.36

---

## RECOMMENDED BY LEMO

### Tools

Positionner: [DCE.91.092.BVM](#)

Extractor: [DCF.91.090.2LT](#)

### Cables

*LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*