



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939 SK3150B-L

### **Features**

- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
- For Surface Mount Applications
- Extremely Low Thermal Resistance
- Easy Pick And Place
- Halogen free available upon request by adding suffix "-HF"
- High Temp Soldering: 260 °C for 10 Seconds At Terminals
- High Current Capability With Low Forward Voltage
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

### **Maximum Ratings**

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance; 70°C/W Junction To Ambient

MCC Catalog	Device Marking	Maximum Recurrent	Maximum RMS	Maximum DC
Number		Peak Reverse Voltage	Voltage	Blocking Voltage
SK3150B-L	SK3150B	150V	105V	150V


# Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	3.0A	T <sub>J</sub> = 120°C
Peak Forward Surge Current	I <sub>FSM</sub>	80A	8.3ms, half sine
Maximum			
Instantaneous Forward Voltage	.,	001/	
	$V_{F}$	.86V	I <sub>FM</sub> = 3.0A; T <sub>J</sub> = 25°C*
Maximum DC			
Reverse Current At	$I_R$	0.2mA	T <sub>C</sub> = 25°C
Rated DC Blocking		5.0mA	T <sub>C</sub> = 100°C
Voltage			
Typical Junction	$C_{J}$	100pF	Measured at
Capacitance			1.0MHz, V <sub>R</sub> =4.0V


<sup>\*</sup>Pulse test: Pulse width 200 µsec, Duty cycle 2%

Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.

# 3 Amp Schottky Rectifier 150 Volts



DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.160	.185	4.06	4.70		
В	.130	.155	3.30	3.94		
С	.006	.012	0.15	0.31		
D	.030	.060	0.76	1.52		
E	.200	.220	5.08	5.59		
F	.079	.096	2.00	2.44		
G	.075	.087	1.91	2.21		
Н	.002	.008	0.05	0.203		




www.mccsemi.com

# SK3150B-L



#### FIG. 1-TYPICAL FORWARD CURRENT DERATING CURVE



#### FIG. 3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 5-TYPICAL JUNCTION CAPACITANCE




FIG. 2-TYPICAL FORWARD CHARACTERISTICS





FIG. 4-TYPICAL REVERSE CHARACTERISTICS



www.mccsemi.com



### **Ordering Information:**

Device	Packing
SK3150B-LTP	Tape&Reel: 3Kpcs/Reel

Note: Adding "-HF" suffix for halogen free, eg. SK3150B-LTP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.