


# PIN RECEPTACLES

**FOR 0,38 - 0,51 DIAMETER PINS (#11 CONTACT)  
AND 0,38 - 0,56 DIAMETER PINS (#21 CONTACT)  
(SEE SPECIFIC CONTACT RANGE ON PAGE 251)**

## 0548

**0548-0-15-XX-21-XX-10-0**


Solder mount in 0,91 min. mounting hole



## 8975

**8975-0-15-XX-21-XX-10-0**


Solder mount in 0,91 min. mounting hole



## 3016

**3016-0-15-XX-21-XX-10-0**


Solder mount in 0,91 min. mounting hole



## 9548

**9548-0-15-XX-21-XX-10-0**


Solder mount in 0,91 min. mounting hole



## 8637

**8637-0-15-XX-21-XX-10-0**


Solder mount in 0,94 min. mounting hole



## 1407

**1407-0-15-XX-11-XX-10-0**


Solder mount in 1,02 min. mounting hole



## 0553/8553

**X553-X-15-XX-X1-XX-10-0**

Hex press-fit in 1,04 plated through-hole




| Basic Part Number | Length L | Depth N |
|-------------------|----------|---------|
| <b>0553-1</b>     | 3,56     | 3,15    |
| <b>0553-2</b>     | 4,32     | 3,91    |
| <b>0553-3</b>     | 7,16     | 6,76    |
| <b>8553-0</b>     | 6,22     | 5,82    |

## 0566

**0566-X-15-XX-21-XX-10-0**

Solder mount in 1,0 min. mounting hole




| Basic Part Number | Length L |
|-------------------|----------|
| <b>0566-1</b>     | 2,11     |
| <b>0566-2</b>     | 3,51     |

## 0442

**0442-0-15-XX-11-XX-10-0**


Solder mount in 1,02 min. mounting hole



## 0554

**0554-0-15-XX-21-XX-10-0**

Solder mount in 1,02 min. mounting hole



### SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Millimeters

**Tolerances On:** Lengths:  $\pm 0,13$   
Diameters:  $\pm 0,051$   
Angles:  $\pm 2^\circ$



**ORDER CODE: XXXX - X - 15 - XX - XX - 10 - 0**

**BASIC PART #**

**SPECIFY SHELL FINISH:**

- 01** 5,08µm TIN/LEAD OVER NICKEL
- ◆ **80** 5,08µm TIN OVER NICKEL (RoHS)
- ◆ **15** 0,25µm GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

- 02** 2,54µm TIN/LEAD OVER NICKEL
- ◆ **84** 2,54µm TIN OVER NICKEL (RoHS)
- ◆ **27** 0,76µm GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#11 or #21 CONTACT (DATA ON PAGE 251)**

(For alternate contact choices, see group A on page 248)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com