


|   |   |  |   |
|---|---|--|---|
| <h3>8952</h3> <p><b>8952-0-05-XX-00-00-03-0</b><br/>Square press-fit in 2,21 plated thru hole</p> | <h3>8953</h3> <p><b>8953-0-05-XX-00-00-03-0</b><br/>Square press-fit in 1,19 plated thru hole</p> | <h3>7310</h3> <p><b>7310-0-01-XX-00-00-08-0</b><br/>Board edge press-fit</p> | <h3>8816</h3> <p><b>8816-0-00-XX-00-00-03-0</b><br/>Press-fit in 1,45 mounting hole</p> |
|---|---|--|---|

| <h3>8940</h3> <p><b>8940-0-00-XX-00-00-03-0</b><br/>Press-fit in 1,45 mounting hole</p> | <h3>8876</h3> <p><b>8876-0-00-XX-00-00-03-0</b><br/>Press-fit in 1,45 mounting hole</p> | <h3>3120</h3> <p><b>3120-X-00-XX-00-00-08-0</b><br/>Swage mount in 0,86 mounting hole</p> | <table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>3120-1</td> <td>5,21</td> </tr> <tr> <td>3120-2</td> <td>6,35</td> </tr> </tbody> </table> | Basic Part Number | Length A | 3120-1 | 5,21 | 3120-2 | 6,35 |
|---|---|---|---|-------------------|----------|--------|------|--------|------|
| Basic Part Number   | Length A  |   |   |                   |          |        |      |        |      |
| 3120-1  | 5,21  |   |   |                   |          |        |      |        |      |
| 3120-2  | 6,35  |   |   |                   |          |        |      |        |      |



|   |   |
|---|---|
| <h3>SPECIFICATIONS</h3> <p><b>PIN MATERIAL:</b><br/>Brass Alloy 360, 1/2 Hard<br/>(Except Swage pins which are annealed)</p> <p><b>PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY</b></p> <p><b>TOLERANCES ON:</b><br/>LENGTHS: ± 0,13<br/>DIAMETERS: ± 0,05<br/>ANGLES: ± 2°</p> | <p><b>ORDER CODE: XXXX - X - XX - XX - 00 - 00 - 0X - 0</b></p> <p><b>BASIC PART #</b> →</p> <p style="text-align: right;"><b>SPECIFY PIN FINISH:</b></p> <ul style="list-style-type: none"> <li>01 5,08µm TIN/LEAD OVER NICKEL</li> <li>80 5,08µm TIN OVER NICKEL ◊</li> <li>15 0,25µm GOLD OVER NICKEL ◊</li> <li>21 0,51µm GOLD OVER NICKEL ◊</li> <li>34 1,27µm GOLD OVER NICKEL ◊</li> </ul> |
|---|---|

